







SPECIFICATIONS

1. Material:

- (1). Screw: Steel
 - (2). Body: PA66
 - (3). Terminal: Phosphor Bronze
 - (4). Cage: Brass
 - (5). Cover: PA66
 - (6). Screw: Steel
2. Wire range: 12 - 26AWG
 3. Electrical rating: 300V, 10A.
 4. Wire strip length: 5.0mm.
 5. Operating temperature: -40°C to +105°C.
 6. Max torque: 3 in.-lbs.
 7. Insulation resistance: DC 500V, 500 Megohms.
 8. Dielectric withstand: AC 2500V for 1 minute
 9. Breakdown voltage: 4000V
 10. Contact resistance: <10 milliohms
 11. DIM. A = (N + 2)X P
 12. DIM. B = (N - 1)X P
 13. DIM. C = (N + 1)X P
 14. DIM. P (PITCH) = 5.08mm (.200")
 15. N = Number of positions available 2 through 24.
 16. ALL COMPONENTS ARE ROHS COMPLIANT.



RELEASE TO PROD EC NO: ETC2006-0308 DRWN:CYRK 2006/03/23 CHKD:RDEROSS 2006/03/24 APPR:RDEROSS 2006/03/24 A	DESCRIPTION	QUALITY SYMBOLS ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM/IN		SCALE 3:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
				mm	INCH	DRAWN BY C. YORK	DATE 2006/03/16	TITLE 5.08MM, EURO PLUG, VERTICAL REAR WIRE ENTRY WITH MOUNTING ENDS MOLEX INCORPORATED	
			4 PLACES	± ---	±.0015	CHECKED BY R. DEROSS	DATE 2006/03/16		
			3 PLACES	±0.038	±.005	APPROVED BY R. DEROSS	DATE 2006/03/16		
			2 PLACES	±0.13	±.01	MATERIAL NO.	DOCUMENT NO.		
	1 PLACE	±0.3	± ---	SEE SHT. 2	SD-39537-001	SHEET NO. 1 OF 2			
			ANGULAR ± 2 °						
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

