












Neutral conductor, leading switching for Front mounting, Up to 32 A.,
Accessory for main and emergency stop switch 3LD2

Model							
product brand name	SETRON						
design of the product	accessories for 3LD2 main and EMERGENCY-STOP switches						
Accessories							
accessories	leading switching for front mounting, up to 32 A,						
AWG number / as coded connectable conductor cross section							
<ul style="list-style-type: none"> • minimum • maximum 	14 8						
type of connectable conductor cross-sections / for main contacts							
<ul style="list-style-type: none"> • finely stranded / with core end processing • solid or stranded 	1x (1.5 ... 16 mm ²) 1x (1.5...10 mm ²)						
General Product Approval							
	<table border="1"> <thead> <tr> <th>Test Certificates</th> <th>other</th> </tr> </thead> <tbody> <tr> <td>  Confirmation </td> <td>   </td> </tr> <tr> <td> Special Test Certificate </td> <td> Miscellaneous </td> </tr> </tbody> </table>	Test Certificates	other	 Confirmation	 	Special Test Certificate	Miscellaneous
Test Certificates	other						
 Confirmation	 						
Special Test Certificate	Miscellaneous						

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD9220-0B>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD9220-0B>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD9220-0B

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



