



REVERSING CONTACTOR COMBINATION AC-3
11KW/400V,
SIZE S0 AC 24V, 50/60HZ

General details:

Product function		reversing contactor
Size of the contactor		S0
Width	mm	100
Height	mm	86
Depth	mm	91
Item designation		
<ul style="list-style-type: none"> • according to DIN EN 61346-2 • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 		Q K

Control circuit:

Type of voltage / of the controlled supply voltage		AC
Control supply voltage / 1		
<ul style="list-style-type: none"> • at 50 Hz / for AC <ul style="list-style-type: none"> • rated value • at 60 Hz / for AC <ul style="list-style-type: none"> • rated value 	V	24
	V	24
Control supply voltage frequency		
<ul style="list-style-type: none"> • 1 / rated value • 2 / rated value 	Hz	50
	Hz	60

Main circuit:

Operational current / at AC-3 / at 400 V • rated value	A	25
Service power / at AC-3 / at 400 V • rated value	kW	11

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts / per direction of rotation	0
Number of NO contacts / for auxiliary contacts / per direction of rotation	0

Connection type:

Design of the electrical connection / for main current circuit	screw-type terminals
Type of mounting	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022

Ambient conditions:

Ambient temperature • during operating	°C	-25 ... +60
Protection class IP / on the front	IP20	

Certificates/approvals:

General Product Approval	Declaration of Conformity
---------------------------------	----------------------------------



Shipping Approval



Shipping Approval	other
--------------------------	--------------





[other](#)

[Environmental Confirmations](#)

Further information:

- Information- and Downloadcenter (Catalogs, Brochures,...)**
<http://www.siemens.com/industrial-controls/catalogs>
-
- Industry Mall (Online ordering system)**
<http://www.siemens.com/industrial-controls/mall>
-
- CAX-Online-Generator**
<http://www.siemens.com/cax>



last change:

Feb 26, 2013