

Door-coupling rotary operating mechanism IP64 for circuit breaker Size S00...S3, black 330 mm shaft with support







| General technical data                            |     |  |
|---|-----|--|
| Product brand name                                |     | SIRIUS                                   |
| Product designation                               |     | door-coupling rotary operating mechanism |
| Size of the circuit-breaker                       |     | S00, S0, S2, S3                          |
| Design of the product                             |     | standard                                 |
| Control version of the switch operating mechanism |     | long shaft                               |
| Suitability for use                               |     | Circuit breaker S00, S0, S2, S3          |
| Protection class IP on the front                  |     | IP64                                     |
| Ambient temperature                               |     |  |
| • during storage                                  | °C  | -50 ... +80                              |
| • during operation                                | °C  | -20 ... +70                              |
| Operating frequency maximum                       | 1/h | 15                                       |
| Color of the actuating element                    |     | black                                    |

| Installation/ mounting/ dimensions |    |              |
|------------------------------------|----|--------------|
| Mounting position                  |    | any          |
| Mounting type                      |    | screw fixing |
| Width                              | mm | 66           |
| Height                             | mm | 66           |
| Depth                              | mm | 50           |

|  |    |      |
|--|----|------|
| <b>Length</b>                              | mm | 330  |
| <b>Diameter</b>                            | mm | 22.5 |
| <b>Required spacing for grounded parts</b> |    |      |
| • forwards                                 | mm | 0    |
| • Backwards                                | mm | 0    |
| • upwards                                  | mm | 0    |
| • at the side                              | mm | 0    |
| • downwards                                | mm | 0    |

## Certificates/ approvals

**Certificate of suitability** CE / UL / CSA

| General Product Approval  | Declaration of Conformity  | Test Certificates   |
|---|--|---|
|  CSA |  UL       |  EAC |
|   |  EG-Konf. | <a href="#">Miscellaneous</a>   |
|   |  | <a href="#">Type Test Certificates/Test Report</a>                                    |

| Shipping Approval  | other  |
|--|--|
|  ABS | <a href="#">Confirmation</a>   |
|  |  VDE |

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2926-0K>

**Cax online generator**


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2926-0K>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RV2926-0K>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV2926-0K&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV2926-0K&lang=en)



last modified:

03/13/2020