

R413R32200000M

aka 413R32200000M

Capacitor, film, 0.22 uF, +/-20% Tol, -40/+110C, Safety: Y2/X1, 300VAC, Lead Spacing=27.5 mm



Dimensions (mm)

Specifications

| ID | Dimension | Tolerance | Manufacturer: | KEMET |
|----|-----------|-----------|-----------------------------|---------------|
| L | 32 | +0.3 | Brand: | Arcotronics |
| H | 22 | +0.1 | Capacitance: | 0.22 uF |
| T | 13 | +0.2 | Temperature Range: | -40/+110C |
| S | 27.5 | +/-0.4 | Rated Temperature: | 105C |
| LL | 4 | +2 | Voltage @ rated temp: | 1000V |
| F | 0.8 | +/-0.05 | Voltage AC: | 300VAC |
| | | | Tolerance: | +/-20% |
| | | | Body Type: | Radial Box |
| | | | Construction: | Wound |
| | | | Application: | Safety: Y2/X1 |
| | | | Dissipation Factor @ 1 kHz: | 0.3% |
| | | | Insulation Resistance: | 100 GOhm |
| | | | Maximum dVdT: | 400v/us |
| | | | UL_1414: | 250V |
| | | | UL_1283: | 300V |
| | | | IEC_60384-14: | 300V |
| | | | EN_132400: | 300V |
| | | | C_22.2_NO.1: | 250V |
| | | | CQC_GB/T 14472: | 300V |
| | | | Package Kind: | Bulk |
| | | | Package Type: | Bag |
| | | | Package Quantity: | 480 |