

Rittal – The System.

Faster – better – everywhere.

Universal light with integral motion detector – SZ 4155.510

Date : Aug 27, 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Universal light with integral motion detector – SZ 4155.510

: 27.08.2019 build on www.rittal.com/ca-en



Discontinued article.

This item will be discontinued on: 30.04.2019 |||This item is being replaced by: 2500300

Product description

Description: Compact 18 W fluorescent tubes with high light output.

Benefits: Simple, fast mounting

Material: Plastic

Supply includes: Universal light
Integral motion detector
Light (bulb)
Light cover
Assembly components

Product features

Dimensions: Height: 95 mm (3.7 ")
Width: 345 mm (14 ")
Depth: 55 mm (2.2 ")

Rated operating voltage: 110 V - 240 V, 1~, 50 Hz/60 Hz

Installation options: TS horizontal profile from roof frames: direct
TS, SE vertical section: with TS adapter bracket
SE sections on front and rear of roof frame: with TS adapter bracket
SE profiles to the side of roof frames: direct
AE, CM, TP: with universal bracket
AE: with rail for interior installation

Operating temperature:	Operation (environment): -15 °C...+45 °C Storage: -20 °C...+70 °C
Power consumption:	18 W
Equipment (electrical):	Ballast: Wide range voltage EB Light (bulb): Compact fluorescent lamp, G24q-3 backplate Integral motion detector: yes Switch (type): Integral, on/off/motion detector mode
Rated insulation voltage:	250 V AC
Rated impulse withstand voltage, phase to phase:	2500 V AC
Protection category:	I (PE conductor)
Connection options:	Power supply through connector Through-wiring (configuration of row of luminaires)
Light – installation type:	Screw fastening
Light cover:	yes
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.88 kg (1.9 lb.)
Copper weight (kg per piece):	0
EAN:	4028177679849
Customs tariff number:	94054095
ETIM 6.0:	EC000321
ETIM 5.0:	EC000321
eCl@ss 8.0/8.1:	27189241
eCl@ss 7.0/7.1:	27189241
eCl@ss 6.0/6.1:	27189241
eCl@ss 5.1/5.1.4:	27189241
Product description:	SZ Universal light, WHD: 343x95x55 mm, 18 W, 110-240 V, 50/60 Hz, with integral

motion detector, UL

Approvals

Approvals:	CSA UL VDE
-------------------	------------------

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity
----------------------	---------------------------