

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [43374-3001](#)  
**Status:** **Active**  
**Overview:** Sabre™  
**Description:** Sabre™ Crimp Terminal, Female, 18-20 AWG, 2.85mm max. Insulation Diameter, Reel Packaged, Tin (Sn) Plated Brass Contact, without TPA

**Documents:**

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)  
[Product Specification PS-43374-001 \(PDF\)](#) [Product Literature \(PDF\)](#)

**General**

Product Family	Crimp Terminals
Series	43374
Application	Power
Comments	Terminal mates to 3.18mm wide x 0.51mm thick flat blade PC tab. Does not contain TPA feature. UL style UL1015 or UL1056
Crimp Quality Equipment Overview	Yes
Product Literature Order No	Sabre™ 987650-5662
Product Name	Sabre™
UPC	884982058798

**Physical**

Durability (mating cycles max)	25
Gender	Female
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.323/g
Packaging Type	Reel
Plating min - Mating	0.508µm
Plating min - Termination	0.508µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	2.85mm max.
Wire Size AWG	18, 20
Wire Size mm²	N/A

**Electrical**

Current - Maximum per Contact	18A
Voltage - Maximum	600V

**Material Info**

**Reference - Drawing Numbers**

Product Specification	PS-43374-001
Sales Drawing	SD-43374-311



**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC Contains SVHC: No**  
**Low-Halogen Status Low-Halogen**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

43374Series

**Mates With**

43178 Male Crimp Terminals

**Use With**

44441 Receptacle Housings

**Application Tooling | [FAQ](#)**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

Description	Product #
FineAdjust™ Applicator for Flat Blade Crimp Terminal, 18-20 AWG, UL 1015 Wire	<a href="#">0639012700</a>
FineAdjust™ Applicator for	<a href="#">0639012800</a>

Flat Blade Crimp  
Terminal, 18-20  
AWG, UL1056 and  
SPT-3 Wire  
T2 Terminator for 0639112700  
Flat Blade Crimp  
Terminals, 18-20  
AWG, UL1015 Wire  
T2 Terminator for 0639112800  
Flat Blade Crimp  
Terminals, 18-20  
AWG, UL1056 and  
SPT-3 Wire

This document was generated on 06/25/2013

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**