



Gel cable joint with connector

RELICON Relilight

Relilight gel cable joints are designed for light installations, especially LED lighting. They are tested according to DIN EN 60998-2-1: 2004 and offer IP68 protection class. The moulding shells are also flame retardant. Depending on the connector type, Relilight can be used either for straight-through or as branch joints. They are suitable for jointing on polymeric cables and wires made of PVC, XLPE, PE, EPR etc. The silicone-based RELICON gel in the Relilight cable joints provides insulation, sealing and mechanical protection in one step. Furthermore, they reduce the workload and total cost of installation.


Application: In low-voltage electrical networks as straight-through or branch joints, e.g. for outdoor light installations, underground, submerged, outdoor, indoor and in wiring ducts.

Features and Benefits

- Moulding shell: two piece, black, re-openable, with strain relief, flame retardant, protection class IP68, 1.3 m
- Filled with Relicon non-toxic gel, high dielectric strength >1kV,
- No mixing, ready to assembly
- UV, ageing and weather resistant
- Compact dimensions, with connector
- Unlimited shelf life
- Certified according to DIN EN 60998-2-1:2004

Content of Set / Kit

- Moulding shells filled with RELICON gel
- Adapter for strain relief (not for No. 435-01650)
- Installation instructions, connector block, screws
- Wire guide (only No. 435-01654)



Relilight gel cable joint.

MATERIAL	Polyamide 6.6 V0 (PA66V0), Silicone (SI)
Colour	Black (BK)
Operating Temperature	-30 °C to +130 °C
Shelf Life	Unlimited

RoHS ✓



**With
connector block!**



**IP68,
1.3 meter**

TYPE	Ø Main Cable	Main Cable mm ² min - max		Branch Cable mm ² min - max		Voltage range	Length (L)	Width (W)	Height (H)	Article-No.
Relilight V2.75 I1	4.8-6	2 x 0.35	2 x 0.75	-	-	250V, 6A	44.0	18.0	17.5	435-01650
Relilight V32.5 I2	6.5-12	3 x 0.5	3 x 2.5	-	-	250V, 16A	100.0	24.0	29.0	435-01651
Relilight V32.5 P1	6.5-12	3 x 0.5	3 x 2.5	3 x 0.5	3 x 2.5	250V, 16A	105.0	44.0	24.0	435-01655
Relilight V41.5 P1	6.5-12	4 x 0.5	4 x 1.5	4 x 0.5	4 x 1.5	250V, 16A	105.0	44.0	24.0	435-01656
Relilight V61.5 I2	6.5-12	6 x 0.5	6 x 1.5	-	-	12V - 24V	100.0	24.0	29.0	435-01652
Relilight V34 P2	7.5-16	3 x 1.5	3 x 4	3 x 1.5	3 x 4	450V, 25A	138.0	78.0	35.0	435-01657
Relilight V36 P2	7.5-16	3 x 1.5	3 x 6	3 x 1.5	3 x 6	450V, 25A	138.0	78.0	35.0	435-01658
Relilight V31.5 U1	8.0-10	3 x 0.5	3 x 1.5	-	-	250V, 16A	38.0	42.5	29.5	435-01653
Relilight V41 U1	8.0-10	4 x 0.5 / 6 x 0.35	4 x 1 / 6 x 0.5	-	-	12V - 24V	38.0	42.5	29.5	435-01654

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

For product specific approvals please contact us under www.HellermannTyton.com