

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [44764-1403](#)  
**Status:** **Active**  
**Overview:** Micro-Fit 3.0™ Connectors  
**Description:** 3.00mm Pitch Micro-Fit 3.0, BMI™ Receptacle Header, Dual Row, Right Angle, with Press-fit Plastic Pegs, 0.80µm Gold (Au) Selective, 14 Circuits

**Documents:**

|  |  |
|--|--|
| <a href="#">3D Model</a>                                 | <a href="#">Test Summary TS-44764-001 (PDF)</a>      |
| <a href="#">Drawing (PDF)</a>                            | <a href="#">RoHS Certificate of Compliance (PDF)</a> |
| <a href="#">Product Specification PS-44300-001 (PDF)</a> | <a href="#">Product Literature (PDF)</a>             |

**Agency Certification**

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

**General**

|                             |   |
|-----------------------------|---|
| Product Family              | PCB Receptacles                           |
| Series                      | <a href="#">44764</a>                     |
| Application                 | Board-to-Board, Power, Wire-to-Board      |
| Overview                    | <a href="#">Micro-Fit 3.0™ Connectors</a> |
| Product Literature Order No | 987650-5984                               |
| Product Name                | Micro-Fit 3.0 BMI™                        |
| UPC                         | 756054398630                              |

**Physical**


|                                |                 |
|--------------------------------|-----------------|
| Circuits (Loaded)              | 14              |
| Circuits (maximum)             | 14              |
| Durability (mating cycles max) | 30              |
| Flammability                   | 94V-0           |
| Glow-Wire Compliant            | No              |
| Material - Metal               | Phosphor Bronze |
| Material - Plating Mating      | Gold            |
| Material - Plating Termination | Tin             |
| Net Weight                     | 3.938/g         |
| Number of Rows                 | 2               |
| Orientation                    | Right Angle     |
| PCB Locator                    | Yes             |
| PCB Retention                  | Yes             |
| PCB Thickness - Recommended    | 1.60mm          |
| Packaging Type                 | Tray            |
| Pitch - Mating Interface       | 3.00mm          |
| Plating min - Mating           | 0.762µm         |
| Plating min - Termination      | 2.540µm         |
| Polarized to PCB               | Yes             |
| Surface Mount Compatible (SMC) | No              |
| Temperature Range - Operating  | -40°C to +105°C |
| Termination Interface: Style   | Through Hole    |

**Electrical**

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 5A   |
| Voltage - Maximum             | 250V |

**Solder Process Data**

|  |                        |
|--|------------------------|
| Duration at Max. Process Temperature (seconds) | 5                      |
| Lead-free Process Capability                   | Wave Capable (TH only) |
| Max. Cycles at Max. Process Temperature        | 1                      |
| Process Temperature max. C                     | 260                    |



**EU RoHS**

**ELV and RoHS Compliant**  
**REACH SVHC Contains SVHC: No**  
**Low-Halogen Status Low-Halogen**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

44764Series

**Mates With**

44428 , 44300 , 44432

## Material Info

### Reference - Drawing Numbers

Product Specification  
Sales Drawing  
Test Summary

PS-44300-001, RPS-44300-001  
SD-44764-001  
TS-44764-001

This document was generated on 11/28/2012

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**