

R46KI3220CK02K

aka 46KI3220CK02K

Capacitor, film, 0.22 uF, +/-10% Tol, -40/+110C, Safety: X2, 275VAC,
Lead Spacing=15 mm



Dimensions (mm)

Specifications

| ID | Dimension | Tolerance |
|----|-----------|-----------|
| L | 18 | +0.3 |
| H | 17.5 | +0.1 |
| T | 6 | +0.2 |
| S | 15 | |
| LL | 18.5 | +/-0.5 |
| F | 0.6 | +/-0.05 |

| | |
|------------------------------------|-------------|
| Manufacturer: | KEMET |
| Brand: | Arcotronics |
| Capacitance: | 0.22 uF |
| Temperature Range: | -40/+110C |
| Rated Temperature: | 105C |
| Voltage @ rated temp: | 560V |
| Voltage AC: | 275VAC |
| Tolerance: | +/-10% |
| Body Type: | Radial Box |
| Construction: | Wound |
| Application: | Safety: X2 |
| Dissipation Factor @ 1 kHz: | 0.1% |
| Insulation Resistance: | 100 GOhm |
| Maximum dVdT: | 400v/us |
| UL_1414: | 250V |
| UL_1283: | 310V |
| IEC_60384-14: | 275V |
| CSA_384-14: | 275V |
| CQC_GB/T 14472: | 275V |
| Package Kind: | T&R |
| Package Size: | 500mm |
| Package Quantity: | 1000 |