



TRANSFORMER SITAS; PHASES:1;
 PN/PN(S6)(KVA):5 /18,5; UPRI(V):400+/-5%;
 USEC(V):230-115; ISEC(A):21,7-43,5; F(HZ):50...60;
 VECTOR GR./SHIELD WNG.:II0 /0; TA/ISOKL:55 /H;
 IP00; TYPE OF TERMINALS:SCREW CONNECTION;
 INSTALLATION:SCREW; EN 61558-2-1, -2-2, -2-4
 >UL/CSA-RECOGNIZED< >CONTROL CIRCUIT
 TRANSFORMER< >ISOLATION TRANSFORMER<

Figure similar

General technical data		
Product designation		transformer SITAS
Product brand name		SIDAC
Operating apparent output rated value	V·A	5 000
Efficiency		0.94
Connection method for transformers		II0
Certificate of suitability		CE / cRUus
Product function		
• Temperature monitoring		No
• Insulation monitoring		No
• Short-circuit and overload proof		No
Number of shielding windings		0
Short-term vector power	V·A	19 000
Relative short-circuit voltage	%	3.9
Inputs		
Phase number of the inputs		1
Input voltage		

• _1 rated value	V	420
• _2 rated value	V	400
• _3 rated value	V	380
Electrical input frequency		
• minimum	Hz	50
• maximum	Hz	60

Outputs

Phase number of the outputs		1
Output voltage		
• _1 rated value	V	230
• _2 rated value	V	115
Electrical output frequency		
• maximum	Hz	60
• minimum	Hz	50

Ambient conditions

Thermal class acc. to IEC 60085		H
Ambient temperature rated value	°C	55
Protection class IP		IP00

Mechanical data

Type of electrical connection		
• at output for main current circuit		screw-type terminals
• at input for main current circuit		screw-type terminals
Mounting type		screws
Construction form of the iron core		UI 180/75
Width	m	0.194
Height	m	0.32
Depth	m	0.169

Certificates/ approvals

General Product Approval	Declaration of Conformity	Shipping Approval	other
---------------------------------	----------------------------------	--------------------------	--------------



[Miscellaneous](#)



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AT3612-5AD40-0FA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4AT3612-5AD40-0FA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AT3612-5AD40-0FA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4AT3612-5AD40-0FA0&lang=en

last modified:

04/04/2020