

5-520532-3 ✓ ACTIVE

## AMPLIMITE


TE Internal #: 5-520532-3

SDL Connectors, Plug, Round Jacketed Cable, 26 AWG / 28 AWG  
Wire Size, .08 – .09 mm<sup>2</sup> / .129 mm<sup>2</sup> / .12 – .15 mm<sup>2</sup> Wire Size, Cable-  
to-Board, 8 Position

[View on TE.com >](#)



Connectors > Audio & Video Connectors > Shielded Data Link > SDL Connectors



Connector & Housing Type: **Plug**

Compatible With Wire & Cable Type: **Round Jacketed Cable**

Wire Size: .08 – .09 mm<sup>2</sup>, .081 mm<sup>2</sup>, .12 – .15 mm<sup>2</sup>, .129 mm<sup>2</sup>

Connector System: **Cable-to-Board**

### Features

#### Product Type Features

Receptacle Configuration	Standard
Connector & Housing Type	Plug
Connector System	Cable-to-Board
Connector & Contact Terminates To	Wire & Cable

#### Configuration Features

Compatible With Wire & Cable Type	Round Jacketed Cable
Number of Positions	8

#### Body Features

Shield Plating Finish	Bright
Shield Plating Material	Tin
Shield Material	Steel

#### Contact Features

	50 μin
Contact Mating Area Plating Material	Gold
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	1.5 A

#### Mechanical Attachment

PCB Mount Retention	Without
Polarization Code	E



Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

### Housing Features

Housing Material	Polycarbonate GF
Housing Color	Smoke Gray
Centerline (Pitch)	1.27 mm[.05 in]

### Dimensions

Conductor Insulation Diameter Range	1.14 – 1.27 mm[.045 – .05 in]
Wire Size	.08 – .09 mm <sup>2</sup> , .081 mm <sup>2</sup> , .12 – .15 mm <sup>2</sup> , .129 mm <sup>2</sup>

### Usage Conditions

Operating Temperature Range	-20 – 80 °C[-4 – 176 °F]
-----------------------------	--------------------------

### Operation/Application

Circuit Application	Signal
---------------------	--------

### Industry Standards

Agency/Standard	CSA, UL
UL Flammability Rating	UL 94V-2

### Other

Audio & Video Connector Comment	Plug assemblies for round cable need a top shield, bottom shield, boot, and ferrule., Prefix no. designates key configuration. Suffix no. is a code for the number of conductors. Prefix & suffix nos. of plug assemblies must match those of the intended mating receptacle. Keys are molded in as an integral part of the plug & receptacle.
---------------------------------	--

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224)



Does not contain REACH SVHC

Halogen Content

Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts

TE Part # 520437-1  
8 SDL FERRULE,BULK PKG

TE Part # 520465-1  
8 SDL RND SHIELD,BTTM,BULK PKG

TE Part # 520853-1  
8 SDL RND PLUG BOOT,BULK PKG

### Customers Also Bought

TE Part #520437-1  
8 SDL FERRULE,BULK PKG

TE Part #520465-1  
8 SDL RND SHIELD,BTTM,BULK PKG

TE Part #520853-1  
8 SDL RND PLUG BOOT,BULK PKG

TE Part #1740317-3  
NECTOR S DISTRIBUTOR ASSY 6 POS BLACK

TE Part #520464-1  
8 SDL RND SHIELD, TOP,BULK PKG

TE Part #1740317-2  
NECTOR S DISTRIBUTOR ASSY 7 POS WHITE

TE Part #10214516-00  
PRESS XDCR M5852-000005-500PG

TE Part #1740316-1  
NECTOR S CODING RING



## Documents

### Product Drawings

[8 SDL RND PLUG ASSY 36 SERIES](#)

English

### CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_5-520532-3\\_AA.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_5-520532-3\\_AA.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_5-520532-3\\_AA.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Product Specifications

[Application Specification](#)

English

### Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

[Instruction Sheet \(U.S.\)](#)

English

[Crimping Die Assemblies 58195-1, 58195-2, 58195-3, and 58195-6](#)

English