


**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [5047545100](#)  
**Status:** **Active**  
**Overview:** [Easy-On FFC FPC Connectors](#)  
**Description:** 0.30mm Pitch Easy-On Back Flip FPC Connector with Lock Terminal, LA75 Series, Right-Angle, Surface Mount, Dual Contact Style, 0.75mm Height, 51 Circuits

**Documents:**

|  |   |
|--|---|
| <a href="#">Drawing (PDF)</a>                              | <a href="#">Application Specification AS-504754-002-001 (PDF)</a> |
| <a href="#">3D Model (PDF)</a>                             | <a href="#">Packaging Specification 5047549200-200 (PDF)</a>      |
| <a href="#">3D Model</a>                                   | <a href="#">RoHS Certificate of Compliance (PDF)</a>              |
| <a href="#">Product Specification 5047540000-000 (PDF)</a> |   |



*Series image - Reference only*

**General**

|                |  |
|----------------|--|
| Product Family | FFC/FPC Connectors                         |
| Series         | <a href="#">504754</a>                     |
| Overview       | <a href="#">Easy-On FFC FPC Connectors</a> |
| Product Name   | Easy-On                                    |
| UPC            | 889056000222                               |

**Physical**

|                                |                        |
|--------------------------------|------------------------|
| Actuator Type                  | Flip                   |
| Circuits (Loaded)              | 51                     |
| Circuits (maximum)             | 51                     |
| Color - Resin                  | Black                  |
| Contact Position               | Dual                   |
| Durability (mating cycles max) | 10                     |
| Mated Height                   | 0.75mm                 |
| Material - Metal               | Copper Alloy           |
| Material - Plating Mating      | Gold                   |
| Material - Plating Termination | Gold                   |
| Material - Resin               | Liquid Crystal Polymer |
| Net Weight                     | 66.564/mg              |
| Number of Rows                 | 1                      |
| Orientation                    | Right Angle            |
| PCB Locator                    | No                     |
| PCB Mounting                   | Surface Mount          |
| PCB Retention                  | None                   |
| Packaging Type                 | Embossed Tape on Reel  |
| Pitch - Mating Interface       | 0.30mm                 |
| Pitch - Termination Interface  | 0.30mm                 |
| Polarized to PCB               | Yes                    |
| Stackable                      | No                     |
| Temperature Range - Operating  | -40° to +105°C         |
| Wire/Cable Type                | FPC only               |

**Electrical**

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 0.3A |
| Voltage - Maximum             | 50V  |

**Material Info**

**Reference - Drawing Numbers**

|                           |                                |
|---------------------------|--------------------------------|
| Application Specification | AS-504754-002-001              |
| Packaging Specification   | 5047549200-200                 |
| Product Specification     | 5047540000-000                 |
| Sales Drawing             | 5047540000-000, 5047541000-000 |

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2020)4578-DC (25  
June 2020)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[504754 Series](#)

This document was generated on 10/06/2020

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**