

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [5052741012](#)  
**Status:** **Active**  
**Overview:** SlimStack Board-to-Board Connectors  
**Description:** SlimStack Board-to-Board Plug, 0.35mm Pitch, SSB RP Series, 0.80 or 0.90mm Mated Height, 2.00mm Mated Width, 10 Circuits, Armor Nail

**Documents:**

|   |  |
|---|--|
| <a href="#">3D Model</a>  | <a href="#">Datasheet (PDF)</a>                      |
| <a href="#">Drawing (PDF)</a>                                   | <a href="#">Product Guide (PDF)</a>                  |
| <a href="#">3D Model (PDF)</a>                                  | <a href="#">RoHS Certificate of Compliance (PDF)</a> |
| <a href="#">Product Specification 5052700001-PS-000 (PDF)</a>   | <a href="#">Reference Guide (PDF)</a>                |
| <a href="#">Packaging Specification 5052749200SPK-200 (PDF)</a> |  |

**General**

|                |   |
|----------------|---|
| Product Family | PCB Headers   |
| Series         | <a href="#">505274</a>                              |
| Application    | Board-to-Board                                      |
| Overview       | <a href="#">SlimStack Board-to-Board Connectors</a> |
| Product Name   | SlimStack   |
| Series Name    | SSB RP  |
| UPC            | 191128462099  |

**Physical**

|                                |                        |
|--------------------------------|------------------------|
| Breakaway                      | No                     |
| Circuits (Loaded)              | 10                     |
| Circuits (maximum)             | 10                     |
| Color - Resin                  | Black                  |
| Durability (mating cycles max) | 30                     |
| Glow-Wire Capable              | No                     |
| Mated Height                   | 0.80mm, 0.90mm         |
| Mated Width                    | 2.00mm                 |
| Material - Metal               | Copper Alloy           |
| Material - Plating Mating      | Gold                   |
| Material - Plating Termination | Gold                   |
| Material - Resin               | Liquid Crystal Polymer |
| Net Weight                     | 4.890/mg               |
| Number of Rows                 | 2                      |
| Orientation                    | Vertical               |
| PCB Locator                    | No                     |
| PCB Retention                  | Yes                    |
| Packaging Type                 | Embossed Tape on Reel  |
| Pitch - Mating Interface       | 0.35mm                 |
| Pitch - Termination Interface  | 0.35mm                 |
| Plating min - Mating           | 0.100µm                |
| Plating min - Termination      | 0.050µm                |
| Polarized to Mating Part       | No                     |
| Polarized to PCB               | No                     |
| Temperature Range - Operating  | -40° to +85°C          |
| Termination Interface: Style   | Surface Mount          |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.3A, 3.0A      |
| Voltage - Maximum             | 50V AC (RMS)/DC |

**Material Info**

**Reference - Drawing Numbers**

|                         |                   |
|-------------------------|-------------------|
| Packaging Specification | 5052749200SPK-200 |
|-------------------------|-------------------|



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2020)4578-DC (25  
June 2020)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[505274 Series](#)

**Mates With**

SlimStack SSB RP Receptacle [505270](#)

This document was generated on 09/15/2020

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**