


5111374-6 Product Details

[Share](#) | [Print](#) | [Email](#)


✔ Active

AMP-LATCH Pin and Pinless Headers

A/L UNIV HDR 26P VERT LG LAT HT

5111374-6 ✔

TE Internal Number: 5111374-6

Product Highlights [View All](#)

- Header
- Header Type = Universal Ejection Pin Headers
- AMP-LATCH Product Line
- Standard Profile
- 26 Positions

[Pricing & Availability](#) ➤

[Request Sample](#) ➤

[Add to My Part List](#) +

[Buy Product through Distributor](#) ➤

Feedback

[Documents](#) | [Features](#) | [Compliance](#)

Please Note:
Use the Product Drawing for all design activity

Product Type Features	
Connector Type	Header
Product Line	AMP-LATCH
Profile ?	Standard
PCB Mounting Orientation ?	Vertical
PCB Mount Retention ?	Without
Mating Connector Lock ?	With
Ejection Latches ?	With
Post Size (mm [in])	0.64 [.025]
PCB Mount Style	Through Hole
Latch Type	Long
Used For	Receptacles With Strain Relief
Board Standoff	With

Mechanical Attachment	
Contact Retention in Housing	Press-Fit
Mounting Ears	With

Electrical Characteristics	
Current Rating (A)	1
Insulation Resistance (MΩ)	1,000

Termination Features	
Termination Post Length (mm [in]) ?	2.79 [0.110]

Dimensions	
PCB Thickness, Recommended (mm [in])	1.57 [0.062]
[Shrouded] End Dimension (mm [in])	3.81 [0.150]

Body Features	
Header Type ?	Universal Ejection Pin Headers
Latch Material	PCT
Latch Color	Red

Contact Features	
Contact Plating, Mating Area, Material ?	Gold Flash over Palladium Nickel or Gold (30) over Nickel
Contact Shape	Square
Contact Base Material	Brass, Phosphor Bronze
Solder Tail Contact Plating	Matte Tin over Nickel (50)

Housing Features	
Centerline, Matrix (mm [in]) ?	2.54 x 2.54 [.100 x .100]
Mating Alignment Type ?	Center & Dual, Military
Housing Style ?	4-Sided
Mating Alignment	With
Housing Material	PCT GF
Housing Color	Red

Configuration Features	
Number of Positions ?	26
Shrouded	Yes
Post Number(s) Omitted	None

Industry Standards	
RoHS/ELV Compliance ?	RoHS compliant, ELV compliant
Lead Free Solder Processes ?	Pin-in-Paste capable to 245°C, Reflow solder capable to 245°C, Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

RoHS/ELV Compliance History	Always was RoHS compliant
Approved Standards	UL Recognized, CSA Certified

Conditions for Usage	
Temperature Rating ?	High

Packaging Features	
Package Type	Loose Piece - Tray

Other	
Brand	AMP

Comment
Pin headers in 10- and 14-position sizes have only one slot for snap-in polarizer (military polarization), located as shown.; Pin headers in 10-position size have only slot for dual polarization, located as shown.

Related Products

Not quite the product you're looking for?

[Find Similar Products](#)

[View Part in Product Feature Selector](#)

[Check for Tooling](#)

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [Global Accessibility Statement](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed

