




CONNECTORS

PCI & PCI EXPRESS CONNECTORS



✓ Active

TE CONNECTIVITY (TE)

CONNECTOR ASSEMBLY, DUAL POSITIONS, .050

PCI EXPRESS

5145169-8

TE Internal Number: 5145169-8

EU RoHS Compliant

EU ELV Compliant

Number of Positions 184

Centerline (Pitch) 1.27 mm [.05 in]

Termination Post Length 3.18 mm [.125 in]

Contact Mating Area Plating Thickness (µin) 30

PCB Mounting Orientation Vertical

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

DOCUMENTATION

Product Drawings

CONNECTOR ASSEMBLY, 92 DUAL POSITION, .050 SERIES, STANDARD EDGE

PDF (TIFF AVAILABLE)

English

CAD Files

3D PDF

PDF

English

Customer View Model

2D_DXF.ZIP

English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Specifications

Application Specification

Card Edge Printed Circuit (PC) Board Connectors

PDF

English

Product Specification

Connector, Card Edge, .050 Centerline

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

PCB Mounting Orientation Vertical

Type of Connector Card Edge

Product Type Connector

Configuration Features

Number of Positions 184

Ejector Without

Number of Hold-Downs 3

Electrical Characteristics

Voltage (VAC) 203

Operating Voltage (VAC) 203

Body Features

Hold-Down Material Brass

Weight (g) 21.627

Bus Width 64 Bit

Contact Features

Solder Tail Contact Plating Material Tin over Nickel

Contact Mating Area Plating Thickness (µin) 30

Contact Base Material Phosphor Bronze

Contact Mating Area Plating Material Gold

Solder Tail Contact Plating Thickness (µm) 2.537

Termination Features

Termination Post Length 3.18 mm [.125 in]

Mechanical Attachment

PCB Mounting Style Through Hole

PCB Mount Retention Type Hold-Down Posts

Housing Features

Centerline (Pitch) 1.27 mm [.05 in]

Housing Color Natural

Hold-Down Plating Material Tin over Nickel

Housing Material High Temperature Thermoplastic

Dimensions

Width 8.88 mm [.35 in]

PCB Thickness (Accepted) 1.57 mm [.062 in]

Length 128 mm [5.039 in]

Usage Conditions

Operating Temperature Range (°C) -55 – 85

Operation/Application

Pick and Place Cover Without

Industry Standards

Bus Type PCI

Packaging Features

Packaging Method Box

Packaging Quantity 35

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
