


Mod. 5218 B

COPOLYMER POLYPROPYLENE WATERPROOF CASE



Metric mm-Kg-C°



INTERNAL DIMENSIONS

L Length	520 mm
W Width	285 mm
D Depth	180 mm
Lid	30 mm
Base	150 mm


EXTERNAL DIMENSIONS

L Length	550 mm
W Width	350 mm
D Depth	200 mm

OTHER DATA

Weight empty	3.75 Kg
Weight with foam	4.30 Kg
Weight with custom foam	Kg
Volume	26.6 lt
Buoyancy	20 Kg/max
Operating temperature	°C min -33 / max +90

Imperial in-lbs-F°



INTERNAL DIMENSIONS

L Length	20 1/2 in
W Width	11 1/4 in
D Depth	7 1/16 in
Lid	1 3/16 in
Base	5 7/8 in

EXTERNAL DIMENSIONS

L Length	21 5/8 in
W Width	13 3/4 in
D Depth	7 7/8 in

OTHER DATA

Weight empty	8.26 lbs
Weight with foam	9.47 lbs
Weight with custom foam	lbs
Volume	7.02 gal
Buoyancy	44.09 lbs/max
Operating temperature	°F min -27.4 / max +194

Mod. 5218 B

ACCESSORIES



PATENTED COMBINATION PADLOCK

Designed to fit snug to the Explorer case mould so as not to swing out



PATENTED HEAVY DUTY BRASS PADLOCK WITH KEYS

Designed to fit snug to the Explorer case mould so as not to swing out



TSA APPROVED PADLOCK WITH COMBINATION

The new TSA approved padlocks allow tsa® airport security agents to open the case without destroying the lock. TSA agents are trained to recognize the travel sentry certified logo and should not break the case lock.



FOAM SET FOR CASE 5218

Layers of pre cubed foam for the bottom and convoluted foam for the lid



BLIND INSERT

Kit includes 6 pcs.

Whenever the slots are not going to be used for in-built applications, those can be closed by blind inserts that will give the case a better and finished interior look.



METAL BRACKET

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



PLASTIC BRACKET

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly

CONVOLUTED FOAM SET FOR CASE 5218

(includes 2 pcs.)



LID PANEL WITH ORGANIZED POUCHES

Practical and robust lid panel with pouches, ideal for small accessories and documents.

Suitable for cases 5218 and 5221.

Color: black.



PROTECTIVE SLEEVE FOR PC 13"-13.3"

Protective padded notebook sleeve. Protects the laptop from shocks and scratches.



PADDED DIVIDER FOR 5218-5221

Padded dividers with internal adjustable partitions. Ideal to protect and transport any kind of sensitive equipment.

Thanks to their modularity, they can be easily combined.



FEATURES



By releasing the back screw, lid becomes set to slide-off when opened at 70°



Stainless steel clip-covers, to grant a better resistance to abrasion.



New pull release latch grants additional safety and avoids accidental opening



Polycarbonate removable label



Automatic pressure release valve.



Load tested handle, reinforced with corrosion proof steel pins



Internal slots for optional panel mounting brackets or panel mounting rings



(Art. NEOSEAL + nr. art.)



(Art. LABELCOVER + nr. art.)



PVC waterproof ID removable label