


Mod. 5326 B

COPOLYMER POLYPROPYLENE WATERPROOF CASE



Metric mm-Kg-C°



INTERNAL DIMENSIONS

L Length	538 mm
W Width	405 mm
D Depth	250 mm
Lid	60 mm
Base	190 mm


EXTERNAL DIMENSIONS

L Length	627 mm
W Width	475 mm
D Depth	292 mm

OTHER DATA

Weight empty	10 Kg
Weight with foam	11.25 Kg
Weight with custom foam	0 Kg
Volume	53 lt
Buoyancy	37.20 Kg/max
Operating temperature	°C min -33 / max +90

Imperial in-lbs-F°



INTERNAL DIMENSIONS

L Length	21 3/16 in
W Width	15 15/16 in
D Depth	9 13/16 in
Lid	2 3/8 in
Base	7 1/2 in

EXTERNAL DIMENSIONS

L Length	24 11/16 in
W Width	18 11/16 in
D Depth	11 1/2 in

OTHER DATA

Weight empty	22.04 lbs
Weight with foam	24.80 lbs
Weight with custom foam	0 lbs
Volume	14 gal
Buoyancy	82.01 lbs/max
Operating temperature	°F min -27.4 / max +194

Mod. 5326 B

ACCESSORIES

PADDED BAG WITH ADJUSTABLE DIVIDERS



Highly durable padded bag with rubber coated handle and robust zipper with lockable Velcro pull zipper. Practical external front pouch for documents, removable shoulder strap and rubber feet on the bottom to grant better grip. Internal adjustable padded dividers for flexible configuration. Ideal to protect sensitive equipment (ie electronic, photographic, broadcasting, medical etc.). Suitable for cases 5325-5326. Color: black.

PATENTED COMBINATION PADLOCK



Designed to fit snug to the Explorer case mould so as not to swing out

PATENTED HEAVY DUTY BRASS PADLOCK WITH KEYS



Designed to fit snug to the Explorer case mould so as not to swing out

TSA APPROVED PADLOCK WITH COMBINATION



The new TSA approved padlocks allow tsa® airport security agents to open the case without destroying the lock. TSA agents are trained to recognize the travel sentry certified logo and should not break the case lock.

FOAM SET FOR CASE 5325 AND 5326

Layers of pre cubed foam for the bottom and convoluted foam for the lid



BLIND INSERT

Kit includes 6 pcs.

Whenever the slots are not going to be used for in-built applications, those can be closed by blind inserts that will give the case a better and finished interior look.



METAL BRACKET

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly



PLASTIC BRACKET

Kit includes 6 pcs.

All models (except for the 1908) are internally equipped with specific slots, to apply the optional metal or plastic brackets which provide either a panel's fixing points or a fix mechanical joint inside the case, to build more complete applications. This way the case becomes a real workstation, rather than just a carrying container. As the panel mounting brackets are mechanically fixed by screws, they can be removed when necessary. The dedicated screws allow the case to remain waterproof, and help the panels to be removed easily and quickly

CONVOLUTED FOAM SET FOR CASE 5325 AND 5326

(includes 2 pcs.)



LID PANEL WITH ORGANIZED POUCHES

Practical and robust lid panel with pouches, ideal for small accessories and documents.

Suitable for cases 5325 and 5326.

Color: black.



PROTECTIVE SLEEVE FOR PC 13"-13.3"

Protective padded notebook sleeve. Protects the laptop from shocks and scratches.

TOP COVER FOR DIV53

Top covers available for larger models: they can be easily fixed on the dividers by Velcro strips. Ideal to protect and keep items in place.



PADDED DIVIDER FOR 5325-5326

Padded dividers with internal adjustable partitions. Ideal to protect and transport any kind of sensitive equipment. Thanks to their modularity, they can be easily combined.



FEATURES



Internal slots for optional panel mounting brackets or panel mounting rings



(from model 3818 on)



(Art. NEOSEAL + nr. art.)



The internal stop ring prevents valve from being completely extracted (Art. PURGEVALVE.B)



(Art. LABELCOVER + nr. art.)





By releasing the back screw, lid becomes set to slide-off when opened at 70°




Asa de carga comprobada, reforzada con pasadores de acero a prueba de corrosión



4 stainless steel clip-covers on the two frontal outer padlock points, to grant a better resistance to abrasion.





Additional fixing points on the lid.