



### Cable and Fibre Type

Grade of the cable: LSZH

Fibre type (ISO/IEC 11801-2002)	Outer Sheath Colour	
62.5/125	OM1	Orange
50/125	OM2	Orange
50/125	OM3	Purple
09/125	OS1	Yellow

### Optical Performance (IEC 61300-3-4):

Multimode (@ 1300nm)

Max. IL - 0.30dB Typical: 0.20dB

Singlemode: (@1310nm and/or 1550nm)

E-2000: Max. IL - 0.30dB Typical: 0.20dB Return Loss: >50dB

LC: Max IL - 0.30dB Typical: 0.20dB Return Loss: >50dB

### RoHS Compliant

**Coiling Diameter:** Coiling Diameter of the patchcord shall be greater than 200mm

**Packing:** Each product shall be individually bagged and identified with a unique number printed on an ID label affixed to the product. Also, each product will be supplied with a Test Certificate.

Id No.	Description	Ea
1.	E2000 Connector	1
2.	E2000 Boot	1
3.	SC Connector	1
4.	SC Boot	1
5.	Identification Label	1
6.	2.8mm Simplex Cable (L m)	1

REV	DESCRIPTION	DATE	DRN	APD	REV	DESCRIPTION (REVISION RECORD)	DATE	DRN	APD
1									

  

FINISH	SCALE	TOLERANCES UNLESS OTHERWISE SPECIFIED:	PART NO.	DRG/REV NO.	REV	QIA	VER	SIGNATURE	DATE
-	Not to Scale	0 P.L.C ± 0.04 1 P.L.C ± 0.04 2 P.L.C ± 0.04 3 P.L.C ± 0.04 4 P.L.C ± 0.04 2 ANG	E2000-SC Duplex PATCHCORD		01				

  

ALL DIMENSIONS IN MM	ANGLES	2 ANG	1

  

REV	DESCRIPTION	DATE	DRN	APD	REV	DESCRIPTION (REVISION RECORD)	DATE	DRN	APD
1									