

# CALRAD

## 55 Series - SVGA, HDTV Adapter Cables

### 55-873 SHIELDED RGB VIDEO CABLES

Used to connect HDTV satellite receivers to HDTV with RGB inputs. Both styles utilize HD15 Male connectors with either RCA or BNC RGB male ends. Overall cable O.D. .37". Mini 75 ohm coax cable O.D. .1".

#### Male HD15 to 3 RCA Males

55-873-RCA-6.....	6 ft.
55-873-RCA-12.....	12 ft.
55-873-RCA-20.....	20 ft.
55-873-RCA-25.....	25 ft.
55-873-RCA-35.....	35 ft.
55-873-RCA-50.....	50 ft.

#### Male HD15 to 3 BNC Males

55-873-BNC-6.....	6 ft.
55-873-BNC-12.....	12 ft.
55-873-BNC-20.....	20 ft.



### 55-866 SVGA/HDTV SHIELDED VIDEO COMPUTER CABLE


15 Pin HD male to (75 Ohm) 5 BNC (male or female) or RCA male nickel plated connectors. RGB video + Sync. color coded cables. Overall cable O.D. .37". Mini 75 ohm coax cable O.D. .1".

#### Male HD15 to 5 BNC Males

55-866-1.....	1 ft.
55-866-3.....	3 ft.
55-866-6.....	6 ft.
55-866-10.....	10 ft.
55-866-12.....	12 ft.
55-866-15.....	15 ft.
55-866-20.....	20 ft.
55-866-25.....	25 ft.
55-866-35.....	35 ft.
55-866-50.....	50 ft.
55-866-100.....	100 ft.
55-866-250.....	bulk cable 250 ft.

#### Male HD15 to 5 RCA Males

55-866-RCA-1.....	1 ft.
55-866-RCA-3.....	3 ft.
55-866-RCA-6.....	6 ft.
55-866-RCA-12.....	12 ft.
55-866-RCA-15.....	15 ft.
55-866-RCA-20.....	20 ft.
55-866-RCA-25.....	25 ft.
55-866-RCA-35.....	35 ft.
55-866-RCA-50.....	50 ft.



#### Female HD15 to 5 BNC Males

55-866F-3.....	3 ft.
55-866F-6.....	6 ft.
55-866F-10.....	10 ft.
55-866F-12.....	12 ft.
55-866F-25.....	25 ft.

### 55-622 SHIELDED RGB/HV CABLE MOUNTED IN A STAINLESS STEEL WALL PLATE

DB15HD female to 5 BNC females. Premium breakout cable allows direct conversion of 5 BNC, RGB+HV cables to DB15HD connector for HDTV, video projector applications. True 75 ohm connectors and cable for accurate video and sync transfers. Length 1'. Use with Calrad 55-611, 55-612 molded cables or other RGB+HV cables.



### 55-620 DB15HD FEMALE TO 5 BNC FEMALE RGB/HV CABLE

Premium signal breakout cable. Allows direct conversion of a 5 BNC, RGB+HV cable to DB15HD connector for HDTV, video projector applications. True 75 ohm connectors and cable for accurate video and sync signal transfers. Overall cable O.D. .37".

55-620-1.....	1 ft.
55-620-3.....	3 ft.
55-620-6.....	6 ft.



### 55-621

#### SHIELDED DB15HD MALE TO 5 BNC FEMALE RGB/HV CABLE

Premium signal breakout cable. Allows direct conversion of a 5 BNC, RGB+HV cable to DB15HD connector for HDTV, video projector applications. True 75 ohm connectors and cable for accurate video and sync signal transfers. Overall cable O.D. .37".

55-621.....	6 Inches	55-621-6.....	6 ft.
55-621-1.....	1 ft.	55-621-10.....	10 ft.
55-621-3.....	3 ft.	55-621-12.....	12 ft.

