



- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

- how to purchase
- [sales contacts](#)
  - [stock check](#)

search

Product Line Search

Please select a Product Line to search.

---

Part # / Text Search

Part No.:


Text Search:

- quick links
- [Dialight Corporate Video](#)
  - [Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. \*\*View PDF File\*\*](#)
  - [Application Notes](#)
  - [FAQs](#)
  - [Dialight Ltd \(UK\)](#)
  - [Dialight Garufo](#)
  - [Dialight BLP](#)
  - [LumiDrives](#)

Circuit Board Indicators - Through Hole Indicators	
P/N# 5513202F	3 mm Lens
Description	3 mm Backlighting Single
Package Options	100 Pieces Per Bag
Product Type	Through Hole Indicators
Sub Product Type	with Single Housing
Configuration	3 mm Lens
Viewing	Right Angle
Viewing Angle	80
Test Current (mA)	20mA

Absolute Maximum Ratings (Ta = 25 °)	
Solder Temp	260Å° for 5 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C



### Operating Characteristics

LED Position	
Color	Red / Yellow
Lamp Type	Bi-Color / Bi-Color
LED Type	
Intensity Min (mcd)	1.7 / 1.7
Intensity Typ (mcd)	5.6 / 5.6
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	
Fwd Voltage Max	
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	100 / 60
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

**Distributor Stock Check**

Check stock with our distributors now.