




PART NUMBER	POS. 1	POS. 2	POS. 3	POS. 4	POS. 5	POS. 6	POS. 7	POS. 8
553-0008-811	BLANK	GREEN	BLANK	GREEN	BLANK	BLANK	BLANK	BLANK
553-0008-812	RED	YELLOW	RED	YELLOW	BLANK	BLANK	BLANK	BLANK
553-0008-813	RED	YELLOW	RED	YELLOW	RED	YELLOW	RED	YELLOW
553-0008-814	RED	YELLOW	BLANK	BLANK	BLANK	BLANK	BLANK	BLANK
553-0008-815	RED	YELLOW	BLANK	BLANK	BLANK	BLANK	BLANK	GREEN

REV.	ECN NO.	REVISIONS	DRN.	CKD.	APP.	DATE
C	—	ADDED 553-0008-815 TO DWG.	LR		N.O.	12-12-95
D	—	ON P/N 553-0008-815 POS. 2 YELLOW WAS BLANK, POS. 5 BLANK WAS YELLOW.	LR		N.O.	2-2-96
E	—	REVISED RED LED SPECS; ADDED NOTE 1.	TC	DC	N.O.	10-30-98
F	—	LED LEAD TRIM .130 ±.010 WAS .110 ±.015. CHANGED GREEN LED SPEC.	DC	Y.C.	N.O.	3-5-99
G	—	REVISED YELLOW LED SPECS.	TC			



RECOMMENDED PC BOARD HOLE PATTERN



OPERATING CHARACTERISTICS AT T_A = 25 C°

SYMBOL	PARAMETER	COLOR	MIN	TYP	MAX	UNITS	TEST COND.
V _F	FORWARD VOLTAGE	RED		2.0	2.8	V	I _F = 20 mA
		YELLOW		2.1	2.8	V	I _F = 20 mA
		GREEN		2.1	2.8	V	I _F = 20 mA
V _R		ALL	5			V	I _R = 100 μA
λ _{PK}	PEAK WAVELENGTH	RED		635		nm	MEASURED AT PEAK
		YELLOW		585		nm	MEASURED AT PEAK
		GREEN		565		nm	MEASURED AT PEAK
I _V	LUMINOUS INTENSITY	RED	7.4	10.0		mc d	I _F = 10 mA
		YELLOW	7.4	10.0		mc d	I _F = 10 mA
		GREEN	4.7	12.6		mc d	I _F = 10 mA

NOTE:
1. DIALIGHT PART NUMBER: 553-0008-811 THRU -815.

THIS DRAWING AND THE CONTENTS HEREIN ARE CONFIDENTIAL AND THE SOLE PROPERTY OF DIALIGHT. REPRODUCTION OF THIS DRAWING OR CONSTRUCTION OF ANY PARTS WITHIN THIS DRAWING ARE FORBIDDEN WITHOUT THE WRITTEN CONSENT OF DIALIGHT.		
SCALE 5:1	DRAWING NUMBER	REV
ALL DIM'S IN: INCHES	C-16016	G
TOLERANCES: UNLESS OTHERWISE SPECIFIED	TITLE	
FRACTIONS: ±1/64 DECIMALS (.XX): ±.020 DECIMALS (.XXX): ±.015	MATERIAL	
ANGLES: ±1°	Dialight	
FINISH:	1913 ATLANTIC AVE. MANASQUAN, N.J. 08736	
FSCM 83330	SHEET OF	FAMILY TABLE: