

FTCB Flat Braid in Coil, Tinned Copper – FTCB15-20 (557250)



- Braids in coil are mainly used for power distribution or earthing applications
- Non-magnetic material
- Tinned finish provides a theft-deterrent appearance



Part Number	FTCB15-20
Article Number	557250
Material	Copper
Finish	Tinned
Wire Diameter	0.006"
Nominal Current	140 A
Cross Section	39.47 kcmil
Number of Wires	1,120
Length	82'
Thickness	0.06"
Width	0.8"
Unit Weight	0.44 lb
Certifications	cURus RoHS
Standard Packaging Quantity	25 m
UPC	78285657893
EAN-13	3479775572505

Unit weight is per meter [3.28'].

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.