



- Circuit Board Indicators
- Panel Mount Indicators
- Solid State Lighting
- Traffic Signals
- Vehicle Lighting
- Rail
- Obstruction Lighting
- Hazardous Area Lighting
- Heliport Lighting

#### how to purchase

-  [sales contacts](#)
-  [stock check](#)

#### search

##### Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

##### Part # / Text Search

Part No.:

Text Search:

search

#### quick links

##### Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

##### Application Notes FAQs

Dialight Ltd (UK)  
Dialight Garufo  
Dialight BLP  
LumiDrives

#### Circuit Board Indicators - Through Hole Indicators


P/N# **5600508F**

Bi-Pin LED Lamp Single Color

|                  |                         |
|------------------|-------------------------|
| Description      | Bi Pin LED Lamp         |
| Package Options  | 25 Pieces Per Bag       |
| Product Type     | Through Hole Indicators |
| Sub Product Type | Discrete LED            |
| Configuration    | Bi-Pin LED Lamp         |
| Lamp Type        | Single Color            |
| Viewing          | Top View                |
| Viewing Angle    | 24                      |

#### Absolute Maximum Ratings (Ta = 25 °)

|                |                |
|----------------|----------------|
| Operating Temp | -20 to +100° C |
| Storage Temp   | -55 to +100° C |



#### Distributor Stock Check

Check stock with our distributors now.

5600508F

[check stock](#)

#### Operating Characteristics

|                            |              |
|----------------------------|--------------|
| LED Position               |              |
| Color                      | Green        |
| Lamp Type                  | Single Color |
| LED Type                   | Resistor     |
| Intensity Min (mcd)        |              |
| Intensity Typ (mcd)        | 70.0         |
| Intensity Max (mcd)        |              |
| Fwd Voltage Min            |              |
| Fwd Voltage Typ            |              |
| Fwd Voltage Max            |              |
| Dom Wavelength Min (nm)    |              |
| Dom Wavelength Typ (nm)    |              |
| Dom Wavelength Max (nm)    |              |
| Power Dissipation Max (mW) |              |
| Backlighting               |              |
| Pitch Between Vertical     |              |
| Pitch Between Horizontal   |              |
| Lum Intensity Min          |              |
| Lum Intensity Typ          |              |
| Lum Intensity Max          |              |