

- Product Navigation
- Circuit Board Indicators
- Panel Mount Indicators
- Solid State Lighting
- Traffic Signals
- Vehicle Lighting
- Rail
- Obstruction Lighting
- Hazardous Area Lighting
- Heliport Lighting

- how to purchase
- sales contacts
- stock check

search

Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

Part # / Text Search

Part No.:

Text Search:

search

quick links

Dialight Corporate Video


Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives

Circuit Board Indicators - Through Hole Indicators		
P/N#	5640100932F	3 mm Lens
Description	3 mm Tri-Level CBI B-Y-G	
Package Options	5 Pieces Per Bag	
Product Type	Through Hole Indicators	
Sub Product Type	with Tri-Level Housing	
Configuration	3 mm Lens	
Viewing	Right Angle	
Viewing Angle	60	
Test Current (mA)	10mA	

Absolute Maximum Ratings (Ta = 25 °)	
Solder Temp	260Â° for 5 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C



Operating Characteristics				
LED Position	Found in position(s): 1	Found in position(s): 2	Found in position(s): 3	
Color	Blue	Yellow	Green	
Lamp Type	Single Color	Single Color	Single Color	
LED Type	Standard Efficiency	Standard Efficiency	Standard Efficiency	
Intensity Min (mcd)	7.1	7.4	4.7	
Intensity Typ (mcd)	12.5	10.0	12.6	
Intensity Max (mcd)	18			
Fwd Voltage Min				
Fwd Voltage Typ				
Fwd Voltage Max				
Dom Wavelength Min (nm)	465			
Dom Wavelength Typ (nm)				
Dom Wavelength Max (nm)				
Power Dissipation Max (mW)	90	60	100	
Backlighting				
Pitch Between Vertical				
Pitch Between Horizontal				
Lum Intensity Min				
Lum Intensity Typ				
Lum Intensity Max				

Distributor Stock Check

Check stock with our distributors now.

5640100932F

[check stock](#)