



- Product Navigation
- Circuit Board Indicators
- Panel Mount Indicators
- Solid State Lighting
- Traffic Signals
- Vehicle Lighting
- Rail
- Obstruction Lighting
- Hazardous Area Lighting
- Heliport Lighting

- how to purchase
 -  sales contacts
 -  stock check

 search

Product Line Search

Please select a Product Line to search.

Part # / Text Search

Part No.:

Text Search:

 quick links

- Dialight Corporate Video
 - Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)
- Application Notes
 - FAQs
- Dialight Ltd (UK)
 - Dialight Garufo
 - Dialight BLP
 - LumiDrives

Circuit Board Indicators - Through Hole Indicators		
P/N# 56807411114F	3 mm Lens	
Description	3 mm Quad X 4 Backlighting R/G-R/G-R/G-R/G	
Package Options	5 Pieces Per Bag	
Product Type	Through Hole Indicators	
Sub Product Type	with Quad Level Housing	
Configuration	3 mm Lens	
Viewing	Right Angle	
Viewing Angle	60	
Test Current (mA)	10mA	

Absolute Maximum Ratings (Ta = 25 °)	
Solder Temp	260Â° for 5 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C



Operating Characteristics

LED Position	Found in position(s): 1-4
Color	 Red / Green
Lamp Type	Bi-Color / Bi-Color
LED Type	
Intensity Min (mcd)	2.5 / 3.7
Intensity Typ (mcd)	4.7 / 10.0
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	
Fwd Voltage Max	
Dom Wavelength Min (nm)	621 / 569
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	100 / 100
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Distributor Stock Check

Check stock with our distributors now.