



- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N# 5972723602F	1208 Package
Description	SMD 1208 Rt Angle Y/G Smpl Strp
Package Options	20 pcs on Tape
Product Type	Surface Mount Indicators
Sub Product Type	Discrete LED 597 Series
Configuration	1208 Package
Viewing Angle	130 degree
Test Current (mA)	30mA
Absolute Maximum Ratings (Ta = 25 °)	
Solder Temp	260Å° for 5 sec
Operating Temp	-55~+85° C
Storage Temp	-55~+85° C

Distributor Stock Check


Check stock with our distributors now.

5972723602F

[check stock](#)

- [how to purchase](#)
- [sales contacts](#)
- [stock check](#)

[search](#)



Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

[find](#)

Part # / Text Search

Part No.:

Text Search:

[search](#)

[quick links](#)

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes

[FAQs](#)

Dialight Ltd (UK)

Dialight Garufo

Dialight BLP

LumiDrives

Operating Characteristics	
LED Position	
Color	Yellow / Green
Lamp Type	Bi-Color / Bi-Color
LED Type	AllnGaP / AllnGaP
Intensity Min (mcd)	20.0 / 20.0
Intensity Typ (mcd)	30.0 / 35.0
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	2.0 / 2.0
Fwd Voltage Max	2.4 / 2.4
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	75 / 75
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	