

- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N# 5973002302F	PLCC-2 Single Color
Description	SMD LED PLCC R Sample Strip
Package Options	20 pcs on Tape
Product Type	Surface Mount Indicators
Sub Product Type	Discrete LED 597 Series
Configuration	PLCC-2 Package
Lamp Type	Single Color
Viewing Angle	120 degree
Test Current (mA)	19mA

Absolute Maximum Ratings (Ta = 25 °)	
Forward Current Continuous	30 mA
Forward Current Pulse	100 mA
Derating	from 40Å° @ .42mA/Å°C
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C
Peak Wave Length	630

Distributor Stock Check

Check stock with our distributors now.

5973002302F

[check stock](#)

how to purchase

- [sales contacts](#)
- [stock check](#)

search

Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

[find](#)


Part # / Text Search

Part No.:

Text Search:

[search](#)

quick links



Operating Characteristics	
LED Position	
Color	Red
Lamp Type	Single Color
LED Type	AllnGaP
Intensity Min (mcd)	112.5
Intensity Typ (mcd)	140.0
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	2.2
Fwd Voltage Max	2.6
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	72
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes

[FAQs](#)

Dialight Ltd (UK)

Dialight Garufo

Dialight BLP

LumiDrives