

- ? [Circuit Board Indicators](#)
- ? [Panel Mount Indicators](#)
- ? [Solid State Lighting](#)
- ? [Traffic Signals](#)
- ? [Vehicle Lighting](#)
- ? [Rail](#)
- ? [Obstruction Lighting](#)
- ? [Hazardous Area Lighting](#)
- ? [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N#	1206 Package Single Color
5973325402F	
Description	

Region:

Product Line:

Circuit Board Indicators

Reverse Current	100 @ Vr =5V
Forward Current Continuous	20 mA
Forward Current Pulse	48 mA
Derating	from 60° @ .96mA/°C
Reverse Voltage	5 V
Operating Temp	-40~+100° C
Storage Temp	-40~+110° C
Peak Wave Length	522

Distributor Stock Check

Check stock with our distributors now.

5973325402F

Check stock with our distributors now.

5973325402F

RoHS Compliant Product

Please note that the stock check is **only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Please select a Product Line to search.

Circuit Board Indicators

Part No.:

Text Search:

Operating Characteristics	
LED Position	
Color	Green
Lamp Type	Single Color
LED Type	InGaN
Intensity Min (mcd)	150
Intensity Typ (mcd)	680.0
Intensity Max (mcd)	
Fwd Voltage Min	3.3
Fwd Voltage Typ	3.8
Fwd Voltage Max	
Dom Wavelength Min (nm)	525
Dom Wavelength Typ (nm)	84
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	