

 Dialight - Leader in LED Technology























- ? [Circuit Board Indicators](#)
- ? [Panel Mount Indicators](#)
- ? [Solid State Lighting](#)
- ? [Traffic Signals](#)
- ? [Vehicle Lighting](#)
- ? [Rail](#)
- ? [Obstruction Lighting](#)
- ? [Hazardous Area Lighting](#)
- ? [Heliport Lighting](#)


Circuit Board Indicators - Surface Mount Indicators	
P/N#	1206 Package Single Color
5973403602F	
Description	


Region:
Product Line:


Check stock with our distributors now.



Please note that the stock check **is only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.




Please select a Product Line to search.



Part No.:

Text Search:




[Dialight Corporate Video](#)

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp.
[View PDF File](#)

[Application Notes](#)
[FAQs](#)

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)

menu rendered

Reverse Current	100 @ Vr =4V
Forward Current Continuous	20 mA
Forward Current Pulse	80 mA
Derating	from 50Â° @ .4mA/Â°C
Reverse Voltage	4 V
Solder Temp	260Â° for 5 sec
Operating Temp	-55 - +85° C
Storage Temp	-55 - +85° C

 RoHS Compliant Product

Distributor Stock Check

Check stock with our distributors now.



Operating Characteristics

LED Position
Color
Lamp Type
LED Type
Intensity Min (mcd)
Intensity Typ (mcd)
Intensity Max (mcd)
Fwd Voltage Min
Fwd Voltage Typ
Fwd Voltage Max
Dom Wavelength Min (nm)
Dom Wavelength Typ (nm)
Dom Wavelength Max (nm)
Power Dissipation Max (mW)
Backlighting
Pitch Between Vertical
Pitch Between Horizontal
Lum Intensity Min
Lum Intensity Typ
Lum Intensity Max

Copyright 2006 Dialight. All rights reserved | [Privacy Policy](#)

