


Dialight - Leader in LED Technology



- ? [Circuit Board Indicators](#)
- ? [Panel Mount Indicators](#)
- ? [Solid State Lighting](#)
- ? [Traffic Signals](#)
- ? [Vehicle Lighting](#)
- ? [Rail](#)
- ? [Obstruction Lighting](#)
- ? [Hazardous Area Lighting](#)
- ? [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N#	PLCC-2 Single Color
5973904302F	
Description	

Region:
Product Line:
Circuit Board Indicators

Forward Current Continuous	30 mA
Forward Current Pulse	90 mA
Derating	from 40° @ .42mA/°C
Solder Temp	240° for 20 sec
Operating Temp	-40~+100° C
Storage Temp	-40~+100° C

Distributor Stock Check

Check stock with our distributors now.

5973904302F



Check stock with our distributors now.



5973904302F

Please note that the stock check is **only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Please select a Product Line to search.

Circuit Board Indicators

Part No.:

Text Search:

Operating Characteristics	
LED Position	
Color	White
Lamp Type	Single Color
LED Type	InGaN
Intensity Min (mcd)	224
Intensity Typ (mcd)	285.0
Intensity Max (mcd)	450.0
Fwd Voltage Min	3.9
Fwd Voltage Typ	4.3
Fwd Voltage Max	
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	114
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Copyright 2006 Dialight. All rights reserved | [Privacy Policy](#)

[Dialight Corporate Video](#)

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

[Application Notes](#)
[FAQs](#)

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)