

All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to ISO 20860-1, DIN 72594-1 (d)

Material

Housing PBT-GF20 (d)
 Secondary Lock PBT-GF10 (d)

Mechanical data

Mating cycles ≥ 25
 Retention force latch ≥ 110 N
 Retention force primary lock ≥ 80 N
 Retention force secondary lock ≥ 60 N
 Coding efficiency ≥ 40 N

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

Environmental data

Temperature range	-40°C to +105°C
Thermal shock	DIN 72594-2 clause 8.2
Temperature and humidity	DIN 72594-2 clause 8.3
Vibration and mechanical shock	DIN 72594-2 clause 8.1
Dry heat	DIN 72594-2 clause 8.4
RoHS	compliant

Application

Applicable e.g. for following connectors: 59K13O-1xx^{*1)}, 59K13D-1xx^{*1)}, 59K13F-1xx^{*1)}, 59K16A-1xx^{*1)}, 59K16B-1xx^{*1)}















^{*1)} -xx for all available cable variations

Packing

Standard 1500 pcs in box, 1500 pcs in reusable container (d) (e)
 Weight 1.48 g/pce

Coding

Part Number has to be accomplished by codification

Coding	Color	RAL	Part-Number
 A	black	sim. 9005	59Z113-000-A
 B	white	sim. 9001	59Z113-000-B
 C	blue	sim. 5005	59Z113-000-C
 D	bordeauxviolet	sim. 4004	59Z113-000-D
 E	green	sim. 6002	59Z113-000-E
 F	brown	sim. 8011	59Z113-000-F
 G	grey	sim. 7031	59Z113-000-G
 H	violet	sim. 4003	59Z113-000-H
 I	beige	sim. 1001	59Z113-000-I
 K	curry	sim. 1027	59Z113-000-K
 L	carmine red	sim. 3002	59Z113-000-L ^{*2)}
 M	pastel orange	sim. 2003	59Z113-000-M ^{*2)}
 N	pastel green	sim. 6019	59Z113-000-N ^{*2)}
 Z	waterblue	sim. 5021	59Z113-000-Z
	traffic purple	sim. 4006	secondary lock

^{*2)} on request

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

Change History

Rev.	Date	Change
c00	20.01.15	Index clearing up
d00	25.10.17	- Changed Standard: From "500 pcs in box" to "500 pcs in box, 1500 pcs in reusable container" - Material specification of Housing changed: From "PBT" to "PBT-GF20" - Material specification of Secondary Lock changed: From "PBT" to "PBT-GF10" - Added Interface: ISO 20860-1
e00	15.11.21	Packaging sizes updated -old packaging size "500 pcs in box, 1500 pcs in reusable container" -updated to "1500 pcs in box, 1500 pcs in reusable container" Changed font to non-italic

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



©

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Lang	01.04.10	F. Danzl	15.11.21	e00	21-1468	S. Guggenberger	15.11.21