



Connecting terminal, 35 mm² according to UL 489, 480Y/277V for LS 5SJ4...-HG Infeed LS

Model	
product brand name	SENTRON
product designation	Connecting terminal
design of the product	35 mm ² , acc. to UL 489, 480Y/277 V for MCBs 5SJ4...-HG infeed MCB
Supply voltage	
operating voltage / at AC / rated value	1 000 V
operational current / at AC / rated value	160 A
Accessories	
accessories	connection terminal
Connections	
tightening torque	
• minimum	4 N·m
• maximum	4 N·m
type of connectable conductor cross-sections / for copper conductor / stranded	2.5 - 35 mm ²
Mechanical Design	
height	31.1 mm
width	16.2 mm
depth	25.7 mm
length	74.7 mm
net weight	33.6 g

General Product Approval

Declaration of Conformity

[Confirmation](#)



[Miscellaneous](#)



other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3666-0HG>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3666-0HG>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3666-0HG

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



