

Aluminum Capacitors Miniature, Axial Lead, High Reliability



Fig.1 Component outline

FEATURES

- Wide temperature range
- Foil tantalum replacement
- Unique Teflon end seal for long life
- High vibration capability
- Life test 2000 hours at + 125 °C



| QUICK REFERENCE DATA | |
|---|---|
| DESCRIPTION | VALUE |
| Nominal case size Ø D x L in mm | 0.276" x 0.945" [7.0 x 24.0] to 0.374" x 2.677" [9.5 x 68.0] |
| Operating temperature | - 55 °C to + 125 °C |
| Rated capacitance range, C _R | 2.2 µF to 2700 µF |
| Tolerance on C _R | + 10 %, + 50 %; - 10 %, + 75 % |
| Rated voltage range, U _R | 5 WVDC to 250 WVDC |
| Termination | 2 axial leads |
| Life validation test at 125 °C | 2000 hours: Δ CAP ≤ 15 % from initial measurement. Δ ESR ≤ 1.3 x initial specified limit. Δ DCL ≤ initial specified limit. |
| Shelf life at 125 °C | 500 hours: Δ CAP ≤ 10 % from initial measurement. Δ ESR ≤ 1.5 x initial specified limit. Δ DCL ≤ 2 x the initial specified limit. |
| DC leakage current | 0 WVDC to 75 WVDC $I = 0.15 \sqrt{CV}$ I in µA, C in µF, V in Volts 100 WVDC to 250 WVDC $I = 0.15 \sqrt{CV} + 5$ |

| RIPPLE CURRENT MULTIPLIERS | | | | |
|----------------------------|---------|-------------|-----------|--------|
| TEMPERATURE | | | | |
| AMBIENT TEMPERATURE | | MULTIPLIERS | | |
| + 125 °C | | 1.0 | | |
| + 85 °C | | 2.0 | | |
| + 75 °C or less | | 2.4 | | |
| FREQUENCY (Hz) | | | | |
| WVDC | 50 - 60 | 100 - 120 | 300 - 400 | > 1000 |
| 0 - 30 | 0.85 | 1.0 | 1.04 | 1.08 |
| 31 - 250 | 0.80 | 1.0 | 1.30 | 1.40 |

| DIMENSIONS in inches [millimeters] | | | | |
|------------------------------------|-----------------------------|------------------------------|-----------------------------|---------------|
| CASE CODE | BARE CASE | | WITH OUTER INSULATION | |
| | DIAMETER | LENGTH | DIAMETER | LENGTH (max.) |
| KD | 0.281 ± 0.016 [7.14 ± 0.40] | 0.937 ± 0.031 [23.81 ± 0.79] | 0.297 ± 0.031 [7.54 ± 0.79] | 1.00 [25.40] |
| DD | 0.375 ± 0.016 [9.53 ± 0.40] | 0.937 ± 0.031 [23.81 ± 0.79] | 0.391 ± 0.031 [9.92 ± 0.79] | 1.00 [25.40] |
| DE | 0.375 ± 0.016 [9.53 ± 0.40] | 1.125 ± 0.031 [28.58 ± 0.79] | 0.391 ± 0.031 [9.92 ± 0.79] | 1.187 [30.16] |
| DG | 0.375 ± 0.016 [9.53 ± 0.40] | 1.375 ± 0.031 [34.93 ± 0.79] | 0.391 ± 0.031 [9.92 ± 0.79] | 1.437 [36.51] |
| DJ | 0.375 ± 0.016 [9.53 ± 0.40] | 1.625 ± 0.031 [41.28 ± 0.79] | 0.391 ± 0.031 [9.92 ± 0.79] | 1.687 [42.86] |
| DL | 0.375 ± 0.016 [9.53 ± 0.40] | 2.187 ± 0.031 [55.56 ± 0.79] | 0.391 ± 0.031 [9.92 ± 0.79] | 2.249 [57.12] |
| DX | 0.375 ± 0.016 [9.53 ± 0.40] | 2.687 ± 0.031 [68.26 ± 0.79] | 0.391 ± 0.031 [9.92 ± 0.79] | 2.749 [69.82] |

**ORDERING EXAMPLE**

Electrolytic capacitor 600D series: 600D 227 F 010 DE 4

| DESCRIPTION | |
|-------------|---|
| CODE | EXPLANATION |
| 600D | product type |
| 227 | capacitance value (220 μ F) |
| F | tolerance (F = - 10 %/ + 50 %) |
| 010 | voltage rating at 85 °C (010 = 10 V) |
| DE | can size (see dimensions table) |
| 4 | sleeve and sealing (4 = polyester sleeve) |

| ELECTRICAL DATA AND ORDERING INFORMATION | | | | |
|---|----------------|-----------------------------|----------------------------------|--------------------------------------|
| CAPACITANCE (μ F) | PART NUMBER | NOMINAL CASE SIZE D x L | Max. ESR at + 25 °C 120 Hz | Max. RIPPLE at + 125 °C 120 Hz |
| 5 WVDC at + 85 °C . . . 3 WVDC at + 125 °C | | | | |
| 220 | 600D227F005KD4 | 0.281 x 0.937 [7.14 x 23.8] | 1.75 | 0.127 |
| 470 | 600D477F005DD4 | 0.375 x 0.937 [9.53 x 23.8] | 0.813 | 0.221 |
| 680 | 600D687F005DE4 | 0.375 x 1.126 [9.53 x 28.6] | 0.564 | 0.286 |
| 1000 | 600D108F005DG4 | 0.375 x 1.378 [9.53 x 35.0] | 0.388 | 0.377 |
| 1200 | 600D128F005DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 0.32 | 0.477 |
| 1800 | 600D188F005DL4 | 0.375 x 2.185 [9.53 x 55.5] | 0.21 | 0.631 |
| 2700 | 600D278F005DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.14 | 0.851 |
| 7 WVDC at + 85 °C . . . 5 WVDC at + 125 °C | | | | |
| 180 | 600D187F007KD4 | 0.281 x 0.937 [7.14 x 23.8] | 2.121 | 0.115 |
| 390 | 600D397F007DD4 | 0.375 x 0.937 [9.53 x 23.8] | 0.972 | 0.202 |
| 470 | 600D477F007DE4 | 0.375 x 1.126 [9.53 x 28.6] | 0.813 | 0.238 |
| 680 | 600D687F007DG4 | 0.375 x 1.378 [9.53 x 35.0] | 0.564 | 0.312 |
| 1000 | 600D108F007DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 0.388 | 0.406 |
| 1500 | 600D158F007DL4 | 0.375 x 2.185 [9.53 x 55.5] | 0.26 | 0.567 |
| 2200 | 600D228F007DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.175 | 0.761 |
| 10 WVDC at + 85 °C . . . 7 WVDC at + 125 °C | | | | |
| 120 | 600D127F010KD4 | 0.281 x 0.937 [7.14 x 23.8] | 3.18 | 0.094 |
| 330 | 600D337F010DD4 | 0.375 x 0.937 [9.53 x 23.8] | 1.16 | 0.185 |
| 390 | 600D397F010DE4 | 0.375 x 1.126 [9.53 x 28.6] | 0.972 | 0.218 |
| 560 | 600D567F010DG4 | 0.375 x 1.378 [9.53 x 35.0] | 0.673 | 0.286 |
| 820 | 600D827F010DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 0.46 | 0.373 |
| 1200 | 600D128F010DL4 | 0.375 x 2.185 [9.53 x 55.5] | 0.318 | 0.513 |
| 1500 | 600D158F010DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.23 | 0.664 |
| 15 WVDC at + 85 °C . . . 10 WVDC at + 125 °C | | | | |
| 100 | 600D107F015KD4 | 0.281 x 0.937 [7.14 x 23.8] | 3.88 | 0.085 |
| 220 | 600D227F015DD4 | 0.375 x 0.937 [9.53 x 23.8] | 1.75 | 0.15 |
| 330 | 600D337F015DE4 | 0.375 x 1.126 [9.53 x 28.6] | 1.16 | 0.199 |
| 470 | 600D477F015DG4 | 0.375 x 1.378 [9.53 x 35.0] | 0.813 | 0.26 |
| 560 | 600D567F015DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 0.686 | 0.305 |
| 820 | 600D827F015DL4 | 0.375 x 2.185 [9.53 x 55.5] | 0.46 | 0.426 |
| 1200 | 600D128F015DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.32 | 0.563 |

Notes

(1) These values are normally stocked. Other ratings are available on special request.

(2) Type 600D Original Ratings are recommended for replacement applications only.



Aluminum Capacitors
Miniature, Axial Lead, High Reliability

Vishay Sprague

| ELECTRICAL DATA AND ORDERING INFORMATION | | | | |
|---|--------------------|------------------------------------|---|---|
| CAPACITANCE (μF) | PART NUMBER | NOMINAL CASE SIZE D x L | Max. ESR at + 25 °C 120 Hz | Max. RIPPLE at + 125 °C 120 Hz |
| 20 WVDC at + 85 °C . . . 15 WVDC at + 125 °C | | | | |
| 68 | 600D686F020KD4 | 0.281 x 0.937 [7.14 x 23.8] | 4.274 | 0.081 |
| 150 | 600D157F020DD4 | 0.375 x 0.937 [9.53 x 23.8] | 1.962 | 0.142 |
| 220 | 600D226F020DE4 | 0.375 x 1.126 [9.53 x 28.6] | 1.325 | 0.186 |
| 330 | 600D337F020DG4 | 0.375 x 1.378 [9.53 x 35.0] | 0.883 | 0.25 |
| 390 | 600D397F020DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 0.257 | 0.299 |
| 680 | 600D687F020DL4 | 0.375 x 2.185 [9.53 x 55.5] | 0.564 | 0.385 |
| 820 | 600D827F020DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.36 | 0.53 |
| 30 WVDC at + 85 °C . . . 20 WVDC at + 125 °C | | | | |
| 47 | 600D476F030KD4 | 0.281 x 0.937 [7.14 x 23.8] | 3.06 | 0.096 |
| 100 | 600D107F030DD4 | 0.375 x 0.937 [9.53 x 23.8] | 1.50 | 0.162 |
| 150 | 600D157F030DE4 | 0.375 x 1.126 [9.53 x 28.6] | 1.00 | 0.215 |
| 220 | 600D227F030DG4 | 0.375 x 1.378 [9.53 x 35.0] | 0.675 | 0.285 |
| 270 | 600D277F030DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 0.56 | 0.338 |
| 390 | 600D397F030DL4 | 0.375 x 2.185 [9.53 x 55.5] | 0.375 | 0.472 |
| 560 | 600D567F030DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.264 | 0.62 |
| 40 WVDC at + 85 °C . . . 30 WVDC at + 125 °C | | | | |
| 33 | 600D336F040KD4 | 0.281 x 0.937 [7.14 x 23.8] | 4.50 | 0.079 |
| 82 | 600D826F040DD4 | 0.375 x 0.937 [9.53 x 23.8] | 1.824 | 0.147 |
| 100 | 600D107F040DE4 | 0.375 x 1.126 [9.53 x 28.6] | 1.50 | 0.175 |
| 150 | 600D157F040DG4 | 0.375 x 1.378 [9.53 x 35.0] | 1.00 | 0.234 |
| 180 | 600D187F040DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 0.844 | 0.275 |
| 270 | 600D277F040DL4 | 0.375 x 2.185 [9.53 x 55.5] | 0.54 | 0.394 |
| 390 | 600D397F040DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.397 | 0.505 |
| 50 WVDC at + 85 °C . . . 40 WVDC at + 125 °C | | | | |
| 22 | 600D226F050KD4 | 0.281 x 0.937 [7.14 x 23.8] | 6.75 | 0.065 |
| 56 | 600D566F050DD4 | 0.375 x 0.937 [9.53 x 23.8] | 2.65 | 0.122 |
| 68 | 600D686F050DE4 | 0.375 x 1.126 [9.53 x 28.6] | 2.17 | 0.146 |
| 100.0 ⁽¹⁾ | 600D107F050DG4 | 0.375 x 1.378 [9.53 x 35.0] | 1.50 | 0.192 |
| 150 | 600D157F050DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 1.00 | 0.253 |
| 180 | 600D187F050DL4 | 0.375 x 2.185 [9.53 x 55.5] | 0.844 | 0.315 |
| 270 | 600D277F050DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.54 | 0.433 |
| 60 WVDC at + 85 °C . . . 50 WVDC at + 125 °C | | | | |
| 15 | 600D156F060KD4 | 0.281 x 0.937 [7.14 x 23.8] | 9.65 | 0.055 |
| 39 | 600D396F060DD4 | 0.375 x 0.937 [9.53 x 23.8] | 3.85 | 0.102 |
| 47 | 600D476F060DE4 | 0.375 x 1.126 [9.53 x 28.6] | 3.06 | 0.123 |
| 82 | 600D826F060DG4 | 0.375 x 1.378 [9.53 x 35.0] | 1.82 | 0.174 |
| 100 | 600D107F060DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 1.50 | 0.207 |
| 150 | 600D157F060DL4 | 0.375 x 2.185 [9.53 x 55.5] | 1.00 | 0.29 |
| 220 | 600D227F060DX4 | 0.375 x 2.685 [9.53 x 68.2] | 0.675 | 0.388 |

Notes⁽¹⁾ These values are normally stocked. Other ratings are available on special request.⁽²⁾ Type 600D Original Ratings are recommended for replacement applications only.



| ELECTRICAL DATA AND ORDERING INFORMATION | | | | |
|---|--------------------|------------------------------------|---|---|
| CAPACITANCE (μF) | PART NUMBER | NOMINAL CASE SIZE D x L | Max. ESR at + 25 °C 120 Hz | Max. RIPPLE at + 125 °C 120 Hz |
| 75 WVDC at + 85 °C . . . 60 WVDC at + 125 °C | | | | |
| 12.0 ⁽¹⁾ | 600D126F075KD4 | 0.281 x 0.937 [7.14 x 23.8] | 12.3 | 0.048 |
| 27 | 600D276F075DD4 | 0.375 x 0.937 [9.53 x 23.8] | 5.625 | 0.084 |
| 39 | 600D396F075DE4 | 0.375 x 1.126 [9.53 x 28.6] | 3.857 | 0.11 |
| 56 | 600D566F075DG4 | 0.375 x 1.378 [9.53 x 35.0] | 2.64 | 0.144 |
| 82 | 600D826F075DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 1.82 | 0.187 |
| 120 | 600D127F075DL4 | 0.375 x 2.185 [9.53 x 55.5] | 1.227 | 0.261 |
| 150 | 600D157F075DX4 | 0.375 x 2.685 [9.53 x 68.2] | 1.00 | 0.399 |
| 100 WVDC at + 85 °C . . . 75 WVDC at + 125 °C | | | | |
| 6.8 | 600D685F100KD4 | 0.281 x 0.937 [7.14 x 23.8] | 22.5 | 0.036 |
| 22 | 600D226F100DD4 | 0.375 x 0.937 [9.53 x 23.8] | 6.75 | 0.077 |
| 27 | 600D276F100DE4 | 0.375 x 1.126 [9.53 x 28.6] | 5.625 | 0.091 |
| 39 | 600D396F100DG4 | 0.375 x 1.378 [9.53 x 35.0] | 3.857 | 0.12 |
| 56 | 600D566F100DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 2.64 | 0.156 |
| 82 | 600D826F100DL4 | 0.375 x 2.185 [9.53 x 55.5] | 1.824 | 0.215 |
| 120 | 600D127F100DX4 | 0.375 x 2.685 [9.53 x 68.2] | 1.27 | 0.91 |
| 150 WVDC at + 85 °C . . . 100 WVDC at + 125 °C | | | | |
| 3.3 | 600D335F150KD4 | 0.281 x 0.937 [7.14 x 23.8] | 38.30 | 0.028 |
| 6.8 | 600D685F150DD4 | 0.375 x 0.937 [9.53 x 23.8] | 19.16 | 0.046 |
| 12.0 ⁽¹⁾ | 600D126F150DE4 | 0.375 x 1.126 [9.53 x 28.6] | 10.5 | 0.066 |
| 18 | 600D186F150DG4 | 0.375 x 1.378 [9.53 x 35.0] | 6.85 | 0.09 |
| 22.0 ⁽¹⁾ | 600D226F150DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 5.75 | 0.106 |
| 33.0 ⁽¹⁾ | 600D336F150DL4 | 0.375 x 2.185 [9.53 x 55.5] | 3.83 | 0.148 |
| 47 | 600D476F150DX4 | 0.375 x 2.685 [9.53 x 68.2] | 2.61 | 0.197 |
| 200 WVDC at + 85 °C . . . 150 WVDC at + 125 °C | | | | |
| 3.3 | 600D335F200KD4 | 0.281 x 0.937 [7.14 x 23.8] | 38.30 | 0.028 |
| 6.8 | 600D685F200DD4 | 0.375 x 0.937 [9.53 x 23.8] | 19.16 | 0.046 |
| 8.2 | 600D825F200DE4 | 0.375 x 1.126 [9.53 x 28.6] | 15.50 | 0.055 |
| 12 | 600D126F200DG4 | 0.375 x 1.378 [9.53 x 35.0] | 10.50 | 0.073 |
| 18 | 600D186F200DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 6.78 | 0.098 |
| 27.0 | 600D276F200DL4 | 0.375 x 2.185 [9.53 x 55.5] | 4.790 | 0.132 |
| 33.0 | 600D336F200DX4 | 0.375 x 2.685 [9.53 x 68.2] | 3.830 | 0.162 |
| 250 WVDC at + 85 °C . . . 200 WVDC at + 125 °C | | | | |
| 2.2 | 600D225F250KD4 | 0.281 x 0.937 [7.14 x 23.8] | 57.50 | 0.023 |
| 5.6 ⁽¹⁾ | 600D565F250DD4 | 0.375 x 0.937 [9.53 x 23.8] | 23.10 | 0.042 |
| 6.8 ⁽¹⁾ | 600D685F250DE4 | 0.375 x 1.126 [9.53 x 28.6] | 19.16 | 0.05 |
| 10.0 ⁽¹⁾ | 600D106F250DG4 | 0.375 x 1.378 [9.53 x 35.0] | 12.70 | 0.066 |
| 15 | 600D156F250DJ4 | 0.375 x 1.626 [9.53 x 41.3] | 8.23 | 0.088 |
| 22.0 ⁽¹⁾ | 600D226F250DL4 | 0.375 x 2.185 [9.53 x 55.5] | 5.75 | 0.121 |
| 27.0 ⁽¹⁾ | 600D276F250DX4 | 0.375 x 2.685 [9.53 x 68.2] | 4.79 | 0.146 |

Notes

⁽¹⁾ These values are normally stocked. Other ratings are available on special request.

⁽²⁾ Type 600D Original Ratings are recommended for replacement applications only.



Aluminum Capacitors
Miniature, Axial Lead, High Reliability

Vishay Sprague

| ELECTRICAL DATA AND ORDERING INFORMATION - original ratings ⁽²⁾ | | |
|---|------------------|--------------------|
| CAPACITANCE (μF) | CASE CODE | PART NUMBER |
| 7 WVDC at + 85 °C . . . 5 WVDC at + 125 °C | | |
| 220 | DD | 600D227G007DD4 |
| 270 | DE | 600D277G007DE4 |
| 390 | DG | 600D397G007DG4 |
| 560 | DJ | 600D567G007DJ4 |
| 820 | DL | 600D827G007DL4 |
| 1000 | DX | 600D108G007DX4 |
| 10 WVDC at + 85 °C . . . 7 WVDC at + 125 °C | | |
| 100 | KD | 600D107G010KD4 |
| 180 | DD | 600D187G010DD4 |
| 220.0 ⁽¹⁾ | DE | 600D227G010DE4 |
| 330 | DG | 600D337G010DG4 |
| 470 | DJ | 600D477G010DJ4 |
| 680 | DL | 600D687G010DL4 |
| 820 | DX | 600D827G010DX4 |
| 15 WVDC at + 85 °C . . . 10 WVDC at + 125 °C | | |
| 68 | KD | 600D686G015KD4 |
| 82 | KD | 600D826G015KD4 |
| 150 | DD | 600D157G015DD4 |
| 180 | DE | 600D187G015DE4 |
| 270 | DG | 600D277G015DG4 |
| 390 | DJ | 600D397G015DJ4 |
| 560 | DL | 600D567G015DL4 |
| 680 | DX | 600D687G015DX4 |
| 20 WVDC at + 85 °C . . . 15 WVDC at + 125 °C | | |
| 68 | KD | 600D686G020KD4 |
| 100.0 ⁽¹⁾ | DD | 600D107G020DD4 |
| 220 | DG | 600D227G020DG4 |
| 30 WVDC at + 85 °C . . . 20 WVDC at + 125 °C | | |
| 33 | KD | 600D336G030KD4 |
| 47 | KD | 600D476G030KD4 |
| 82.0 ⁽¹⁾ | DD | 600D826G030DD4 |
| 100 | DE | 600D107G030DE4 |
| 120 | DG | 600D127G030DG4 |
| 150.0 ⁽¹⁾ | DG | 600D157G030DG4 |
| 220 | DJ | 600D227G030DJ4 |
| 330 | DL | 600D337G030DL4 |
| 390 | DX | 600D397G030DX4 |
| 40 WVDC at + 85 °C . . . 30 WVDC at + 125 °C | | |
| 50 | DD | 600D506G040DD4 |
| 70 | DE | 600D706G040DE4 |
| 100.0 ⁽¹⁾ | DG | 600D107G040DG4 |
| 140 | DJ | 600D147G040DJ4 |
| 210.0 ⁽¹⁾ | DL | 600D217G040DL4 |
| 50 WVDC at + 85 °C . . . 40 WVDC at + 125 °C | | |
| 22.0 ⁽¹⁾ | KD | 600D226G050KD4 |
| 33 | DD | 600D336G050DD4 |
| 47.0 ⁽¹⁾ | DE | 600D476G050DE4 |
| 56 | DG | 600D566G050DG4 |
| 68 | DG | 600D686G050DG4 |
| 100.0 ⁽¹⁾ | DJ | 600D107G050DJ4 |
| 150.0 ⁽¹⁾ | DL | 600D157G050DL4 |

Notes

⁽¹⁾ These values are normally stocked. Other ratings are available on special request.

⁽²⁾ Type 600D Original Ratings are recommended for replacement applications only.



| ELECTRICAL DATA AND ORDERING INFORMATION - original ratings (2) | | |
|--|------------------|--------------------|
| CAPACITANCE (μF) | CASE CODE | PART NUMBER |
| 60 WVDC at + 85 °C . . . 50 WVDC at + 125 °C | | |
| 17.0 (1) | KD | 600D176G060KD4 |
| 80.0 (1) | DJ | 600D806G060DJ4 |
| 75 WVDC at + 85 °C . . . 60 WVDC at + 125 °C | | |
| 12.0 (1) | KD | 600D126F075KD4 |
| 22.0 (1) | DD | 600D226F075DD4 |
| 33 | DE | 600D336F075DE4 |
| 47.0 (1) | DG | 600D476F075DG4 |
| 68.0 (1) | DJ | 600D686F075DJ4 |
| 100 | DL | 600D107F075DL4 |
| 120.0 (1) | DX | 600D127F075DX4 |
| 100 WVDC at + 85 °C . . . 75 WVDC at + 125 °C | | |
| 8.2 | KD | 600D825F100KD4 |
| 12 | DD | 600D126F100DD4 |
| 15 | DE | 600D156F100DE4 |
| 22 | DG | 600D226F100DG4 |
| 33 | DJ | 600D336F100DJ4 |
| 47.0 (1) | DL | 600D476F100DL4 |
| 68 | DX | 600D686F100DX4 |
| 150 WVDC at + 85 °C . . . 100 WVDC at + 125 °C | | |
| 4.7 (1) | KD | 600D475F150KD4 |
| 5.6 | KD | 600D565F150KD4 |
| 8.2 (1) | DD | 600D825F150DD4 |
| 12.0 (1) | DE | 600D126F150DE4 |
| 18 | DG | 600D186F150DG4 |
| 22.0 (1) | DJ | 600D226F150DJ4 |
| 33.0 (1) | DL | 600D336F150DL4 |
| 56.0 (1) | DX | 600D566F150DX4 |
| 200 WVDC at + 85 °C . . . 150 WVDC at + 125 °C | | |
| 3.3 | KD | - |
| 3.9 | KD | - |
| 5.6 | DD | - |
| 8 | DE | 600D805F200DE4 |
| 8.2 | DE | - |
| 12 | DG | - |
| 15 | DJ | - |
| 27 | DL | - |
| 39.0 (1) | DX | 600D396F200DX4 |
| 250 WVDC at + 85 °C . . . 200 WVDC at + 125 °C | | |
| 2.2 | KD | - |
| 3.3 | KD | 600D335F250KD4 |
| 5.6 (1) | DD | 600D565F250DD4 |
| 6.8 (1) | DE | 600D685F250DE4 |
| 10 | DG | 600D106F250DG4 |
| 12.0 (1) | DJ | 600D126F250DJ4 |
| 22.0 (1) | DL | 600D226F250DL4 |
| 27.0 (1) | DX | 600D276F250DX4 |

Notes

(1) These values are normally stocked. Other ratings are available on special request.

(2) Type 600D Original Ratings are recommended for replacement applications only.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.