



Certifications & Ratings

- RoHS compliant
- NEMA 4X (Watertight only)
- IP66 (Watertight only)

Application


The 609 Series LED Panel Mount Indicators are designed for a variety of applications such as:

- Main power indication
- Remote power indication
- Status indication
- Maintenance and warning indication
- Instrumentation
- ... and many more!

Dimensions

inches [mm]

Protruding




Mechanical Information

- Mounting Hole Size:** 0.374" (9.5 mm)
- Max Panel Thickness:** 0.374" (9.5 mm);
with Gasket: 0.318" (8.0 mm)
- Mounting Torque:** 0.362 lbs/ft (5 kg/cm)

Specifications

- Voltage Options:** 6, 12 & 24 V DC (no resistor required)
- Operating Temp:** -30 °C to +85 °C (-22 °F to +185 °F)
- Storage Temp:** -40 °C to +85 °C (-40 °F to +185 °F)
- Electrical Connection:** Solder terminals
- Housing:** Brass—Chrome or Black Plated
- Terminals:** Copper—Nickel Plated
- Lock washer:** Iron—Nickel Plated
- Nut:** Brass—Nickel Plated

Recessed



Ordering Information 609 Series

Part Number Guide										RoHS Compliant		
6	0	9	-	X	X	X	2	-	X	X	0	F
LED Position				Plating				Voltage				
Protruding		1	1		Chrome		2	6VDC				
Recessed		2	2		Black		3	12VDC				
							4	24VDC				
Color												
Red		1	1		Standard							
Green		2	3		Watertight							
Yellow		3										

Protruding LED

Part Number	Part Number	Color	Voltage (V DC)	Current (mA)	Intensity Typ. (mcd)	Plating
Standard	Watertight					
609-1112-120F	609-1112-320F	Red	6	15	85	Chrome
609-1212-120F	609-1212-320F	Green			115	
609-1312-120F	609-1312-320F	Yellow			90	
609-1112-130F	609-1112-330F	Red	12		85	
609-1212-130F	609-1212-330F	Green			115	
609-1312-130F	609-1312-330F	Yellow			90	
609-1112-140F	609-1112-340F	Red	24		85	
609-1212-140F	609-1212-340F	Green			115	
609-1312-140F	609-1312-340F	Yellow			90	
609-1122-120F	609-1122-320F	Red	6		85	Black
609-1222-120F	609-1222-320F	Green			115	
609-1322-120F	609-1322-320F	Yellow			90	
609-1122-130F	609-1122-330F	Red	12		85	
609-1222-130F	609-1222-330F	Green			115	
609-1322-130F	609-1322-330F	Yellow			90	
609-1122-140F	609-1122-340F	Red	24		85	
609-1222-140F	609-1222-340F	Green			115	
609-1322-140F	609-1322-340F	Yellow			90	

Recessed LED

Part Number	Part Number	Color	Voltage (V DC)	Current (mA)	Intensity Typ. (mcd)	Plating
Standard	Watertight					
609-2112-120F	609-2112-320F	● Red	6	15	85	Chrome
609-2212-120F	609-2212-320F	● Green			115	
609-2312-120F	609-2312-320F	● Yellow			90	
609-2112-130F	609-2112-330F	● Red	12		85	
609-2212-130F	609-2212-330F	● Green			115	
609-2312-130F	609-2312-330F	● Yellow			90	
609-2112-140F	609-2112-340F	● Red	24		85	
609-2212-140F	609-2212-340F	● Green			115	
609-2312-140F	609-2312-340F	● Yellow			90	
609-2122-120F	609-2122-320F	● Red	6		85	Black
609-2222-120F	609-2222-320F	● Green			115	
609-2322-120F	609-2322-320F	● Yellow			90	
609-2122-130F	609-2122-330F	● Red	12		85	
609-2222-130F	609-2222-330F	● Green			115	
609-2322-130F	609-2322-330F	● Yellow			90	
609-2122-140F	609-2122-340F	● Red	24		85	
609-2222-140F	609-2222-340F	● Green			115	
609-2322-140F	609-2322-340F	● Yellow			90	

Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.dialightsignalsandcomponents.com

Warranty Statement: Except for the warranty expressly provided for [herein/above/below], Dialight disclaims any and all other warranties, express or implied, including, without limitation, any warranties of merchantability, fitness for a particular purpose, title, and noninfringement.