

Product data sheet

Specifications

SQUARE D



Adder deck, Harmony 8501X,
screw clamp terminals, 10A
resistive at 600V AC, 4NO, 4
standard contact cartridges

8501XB40

Product availability: Stock - Normally stocked in distribution facility

Main

| | |
|---------------------------|---------------|
| Range of Product | 8501X |
| Relay Type | Control relay |
| Product or Component Type | Adder deck |

Complementary

| | |
|---|---|
| Rated breaking capacity | 6 A 120 V AC inductive control circuit UL 508 |
| | 3 A 240 V AC inductive control circuit UL 508 |
| | 1.5 A 480 V AC inductive control circuit UL 508 |
| | 1.2 A 600 V AC inductive control circuit UL 508 |
| | 10 A <= 600 V AC resistive control circuit UL 508 |
| | 1.1 A 125 V DC inductive control circuit UL 508 |
| | 0.55 A 250 V DC inductive control circuit UL 508 |
| | 0.2 A 301...600 V DC inductive control circuit UL 508 |
| | 4 A 125 V DC resistive control circuit UL 508 |
| 0.8 A 250 V DC resistive control circuit UL 508 | |

| | |
|---|---|
| [Icm] rated short-circuit making capacity | 60 A 120 V AC inductive control circuit UL 508 |
| | 30 A 240 V AC inductive control circuit UL 508 |
| | 15 A 480 V AC inductive control circuit UL 508 |
| | 12 A 600 V AC inductive control circuit UL 508 |
| | 10 A <= 600 V AC resistive control circuit UL 508 |
| | 1.1 A 125 V DC inductive control circuit UL 508 |
| | 0.55 A 250 V DC inductive control circuit UL 508 |
| | 0.2 A 301...600 V DC inductive control circuit UL 508 |
| | 4 A 125 V DC inductive control circuit UL 508 |
| 0.8 A 250 V DC resistive control circuit UL 508 | |

| | |
|----------------------------|---|
| Contacts Configuration | 4 NO 4 standard contact cartridges |
| Electrical Connection | Screw clamp terminals |
| Wire Gauge | AWG 18...AWG 12 copper |
| Terminal Tightening Torque | Control circuit 9.03...12.04 lbf.in (1.02...1.36 N.m) screw terminals |

Environment

| | |
|------------------------|---|
| Product Certifications | CE CSA LR60905 class 3211 02 UL recognized E78403 CCN NKCR2 |
|------------------------|---|

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10CP221159 |
| Discount Schedule | 0CP2 |
| GTIN | 785901537328 |
| Returnability | Yes |
| Country of origin | MX |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Packing Units

| | |
|------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 7.620 in (19.355 cm) |
| Package 1 Width | 3.00 in (7.62 cm) |
| Package 1 Length | 19.355 in (49.161 cm) |
| Package weight(Lbs) | 8.800 oz (249.476 g) |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 2 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 2 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.4 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant By Exemption |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|-------------------------------|---|
| Recyclability potential, in % | 70 |
| Circularity Profile | End of Life Information |
| Take-back | No |

Image of product / Alternate images

Alternative



