



Home > Our Products > Abrasives > Mounted Points & Carbide Burrs > Vitrified Bond Mounted Points >

Features & Benefits

Product Uses

Specifications

Gemini 38A AO Vitrified Bond Mounted Point

GOOD



Make cool cuts while minimizing burn and melt risk with this Gemini 38A mounted point on your power grinder. Its 38A abrasive surface makes fast cuts at relatively low temperatures, extending the mounted point's life, and the high-temperature vitrified bonding resin minimizes grit loss even at high RPMs. Use this mounted point for stock removal, blending, deburring, and finishing or polishing surfaces to a high gloss. This versatile mounted point's wide-grit range makes it an ideal choice for general-purpose work and numerous small jobs.



Abrasive : Aluminum Oxide

Max Operating Speed Guideline : Valid to 1/2"

overhang – see package insert for other overhangs

scroll for more info

FEATURES & BENEFITS

38A abrasive is designed to be cool cutting to minimize burn

High temperature vitrified bond maximizes form holding and life

Wide grit range for stock removal

Good general-purpose choice for numerous

parameters

Features & Benefits

Product Uses

Specifications

PRODUCT USES

Markets	Materials	Machines	Applications
Home & Leisure	Soft Carbon Steels	Die Grinder	Deburring
Paint & Drywall	Tool Steels	Flexible Shaft Grinder	Tool Sharpening
Collision Repair	Super Alloys	Inline Grinder	
Manufacturing & Industry		Pencil Grinder	
Medical Industry		Power Drill	
Transportation			
Energy & Environment			

SPECIFICATIONS

WHERE TO BUY

For some products, additional dimensions and grits are available. Please [contact us](#) if you would like to get other specifications.

1/8 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
	1/8"	1 1/2 In.	B124	38A M/F	91770	6146362
1/4 In.	1/8"	1 1/2 In.	B96	38A M	85900	6146362
3/8 In.	1/8"	1 1/2 In.	B97	38A M	81550	6146362

3/16 In. Diameter

SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
----------------	--------------	----------	----------------	-------------------------	--------

Features & Benefits Product Uses Specifications

7/32 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
-----------	----------------	--------------	----------	----------------	-------------------------	--------

3/8 In.	1/8"	1 1/2 In.	B44	38A M	75840	6146362
---------	------	-----------	-----	-------	-------	---------

1/4 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
-----------	----------------	--------------	----------	----------------	-------------------------	--------

1/2 In.	1/8"	1 1/2 In.	B135	38A M	71340	6146362
---------	------	-----------	------	-------	-------	---------

	1/8"	1 1/2 In.	W163	38A M	59990	6146362
--	------	-----------	------	-------	-------	---------

3/4 In.	1/4"	1 1/2 In.	A24	38A M	56000	6146362
---------	------	-----------	-----	-------	-------	---------

	1/8"	1 1/2 In.	W164	38A M	47880	6146362
--	------	-----------	------	-------	-------	---------

1-1/16 In.	1/4"	1 1/2 In.	A15	38A M	50510	6146362
------------	------	-----------	-----	-------	-------	---------

5/16 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
-----------	----------------	--------------	----------	----------------	-------------------------	--------

5/8 In.	1/8"	1 1/2 In.	B53	38A M	67070	6146362
---------	------	-----------	-----	-------	-------	---------

3/8 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
-----------	----------------	--------------	----------	----------------	-------------------------	--------

	1/8"	1 1/2 In.	B122	38A M	68740	6146362
--	------	-----------	------	-------	-------	---------

1/2 In.	1/8"	1 1/2 In.	W176	38A M	50460	6146362
---------	------	-----------	------	-------	-------	---------

3/4 In.	1/8"	1 1/2 In.	B52	38A M	64810	6146362
---------	------	-----------	-----	-------	-------	---------

	1/8"	1 1/2 In.	B52	38A M	78340	6146362
--	------	-----------	-----	-------	-------	---------

	1/8"	1 1/2 In.	B52	38A M/F	64810	6146362
--	------	-----------	-----	---------	-------	---------

1/8" 1 1/2 In. W177 38A M 38640 6146362

1/2 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
Features & Benefits Product Uses Specifications						
	1/8"	1 1/2 In.	B121	38A M	62420	6146362
1/2 In.	1/8"	1 1/2 In.	B131	38A M	62420	6146362
	1/8"	1 1/2 In.	W185	38A M	42750	6146362
3/4 In.	1/8"	1 1/2 In.	B42	38A M	61320	6146362
1-1/2 In.	1/4"	1 1/2 In.	W188	38A M	31070	6146362
2 In.	1/4"	1 1/2 In.	W189	38A M	26830	6146362

5/8 In. Diameter

SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
1/4"	1 1/2 In.	A26	38A M	48980	61463624397

11/16 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
1-1/4 In.	1/4"	1 1/2 In.	A12	38A M	38050	6146362

3/4 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
1/8 In.	1/8"	1 1/2 In.	W200	38A M	50930	6146362
3/4 In.	1/4"	1 1/2 In.	A39	38A M	44030	6146362
1 In.	1/4"	1 1/2 In.	A23	38A M	40300	6146362
	1/4"	1 1/2 In.	W205	38A M	32950	6146362
1-1/8 In.	1/4"	1 1/2 In.	A5	38A CRS	38550	6146362
	1/4"	1 1/2 In.	A5	38A M	38550	6146362
2-1/2 In.	1/4"	1 1/2 In.	A1	38A CRS	20960	6146362

1/4" 1 1/2 In. A1 38A M 20960 6146362

7/8 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
Features & Benefits Product Uses Specifications						
2 In.	1/4"	1 1/2 In.	A11	38A CRS	25420	6146362
	1/4"	1 1/2 In.	A11	38A M	25420	6146362

1 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
	1/4"	1 1/2 In.	A25	38A M	35510	6146362
1/8 In.	1/8"	1 1/2 In.	W215	38A M	38200	6146362
1/2 In.	1/4"	1 1/2 In.	W218	38A M	37890	6146362
1 In.	1/4"	1 1/2 In.	A21	38A M	35510	6146362
	1/4"	1 1/2 In.	A38	38A M	35510	6146362
	1/4"	1 1/2 In.	W220	38A M	30370	6146362
2 In.	1/4"	1 1/2 In.	W222	38A M	20250	6146362
2-3/4 In.	1/4"	1 1/2 In.	A3	38A CRS	15530	6146362
	1/4"	1 1/2 In.	A3	38A M	15530	6146362

1-1/4 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
1-1/4 In.	1/4"	1 1/2 In.	A4	38A M	28550	6146362

1-1/2 In. Diameter

THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
1/4 In.	1/4"	1 1/2 In.	W235	38A M	25460	6146362
1/2 In.	1/4"	1 1/2 In.	W236	38A-M	25460	6146362
1 In.	1/4"	1 1/2 In.	W237	38A M	25460	6146362

1-1/2 In.	1/4"	1 1/2 In.	W238	38A M	20720	6146362
1-5/8 In. Diameter						
THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
Features & Benefits			Product Uses		Specifications	
3/8 In.	1/4"	1 1/2 In.	A36	38A M	23510	6146362
2 In. Diameter						
THICKNESS	SHANK DIAMETER	SHANK LENGTH	SUBSHAPE	SPECIFICATIONS	MAX OPERATING SPEED RPM	PART #
1 In.	1/4"	1 1/2 In.	W242	38A M	19100	6146362

ABOUT US

Norton has been delivering abrasive solutions to our customers for 130 years and counting. We care to deliver right choices that matter to your market and application...

[Read More >](#)

© Saint-Gobain 2020