



by 1.35mm Pitch,  
Unguided, 10  
Columns, 60 Circuits,  
Plated Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0764603010  
2 Pair Right Angle  
Daughtercard  
Receptacle, 1.90  
by 1.35mm Pitch,  
Left Guided, 10  
Columns, 60 Circuits,  
Plated Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0764603020  
2 Pair Right Angle  
Daughtercard  
Receptacle, 1.90  
by 1.35mm Pitch,  
Left Guided, 10  
Columns, 60 Circuits,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764605010  
2 Pair Right Angle  
Daughtercard  
Receptacle, 1.90  
by 1.35mm Pitch,  
Right Guided, 10  
Columns, 60 Circuits,  
Plated Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0764605020  
2 Pair Right Angle  
Daughtercard  
Receptacle, 1.90  
by 1.35mm Pitch,  
Right Guided, 10  
Columns, 60 Circuits,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764501104  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Open Endwall, 10  
Columns, 60 Circuits,  
Pin Length 4.90mm,  
Plated Through Hole  
Dimension 0.46mm,  
Lead-Free  
Impact™ 100 Ohm 0764501107  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Open Endwall, 10  
Columns, 60 Circuits,  
Pin Length 4.90mm,

Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764501108  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Open Endwall, 10  
Columns, 60 Circuits,  
Pin Length 5.50,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764501117  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Left Endwall, 10  
Columns, 60 Circuits,  
Pin Length 4.90mm,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764501127  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Dual Endwall, 10  
Columns, 60 Circuits,  
Pin Length 4.90mm,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764501137  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Unguided,  
Right Endwall, 10  
Columns, 60 Circuits,  
Pin Length 4.90mm,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764503107  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Left Guided,  
Open Endwall, 10  
Columns, 60 Circuits,  
Pin Length 4.90mm,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764503108  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Left Guided,  
Open Endwall, 10  
Columns, 60 Circuits,

Pin Length 5.50mm,,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764505107  
2 Pair Right Angle  
Male Header, 1.90  
by 1.35mm Pitch,  
Right Guided,  
Open Endwall, 10  
Columns, 60 Circuits,  
Pin Length 4.90mm,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764505108  
2 Pair Right Angle  
Male Header, 1.90  
by 1.35mm Pitch,  
Right Guided,  
Open Endwall, 10  
Columns, 60 Circuits,  
Pin Length 5.50mm,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764507107  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Left Guided,  
Right Endwall, 10  
Columns, 60 Circuits,  
Pin Length 4.90mm,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free  
Impact™ 100 Ohm 0764507108  
2 Pair Right Angle  
Male Header,  
1.90 by 1.35mm  
Pitch, Left Guided,  
Right Endwall, 10  
Columns, 60 Circuits,  
Pin Length 5.50mm,,  
Plated Through Hole  
Dimension 0.39mm,  
Lead-Free

This document was generated on 05/20/2013

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**