

CAN-BUS CABLES ACC. TO ISO 11898



CB 627 CAN-Bus cable with UL recognition

S CB 628 Halogen-free CAN-Bus cable for cable tracks with UL recognition



Marking for S CB 628 06282251:

SAB BRÖCKSKES · D-VIERSEN · S CB 628 2 x 0.25 mm² AWM Style 20235 80°C 300 V CE

CAN-Bus according to ISO 11898. The CAN-Bus cable is applied for the exchange of digital information, control apparatus net (CAN) for faster data transmission/exchange. Application in power supply cable tracks, highly flexible data cables.

item no.	type	no. of pairs/conductors	AWG	nominal outer- ϕ inch	mm	cable weight \approx lbs/ft
▶ 06272251	CB 627	2	24 (\approx 16/34)	0.240	6.1	30
▶ 06272341	CB 627	2	22 (\approx 7/30)	0.252	6.4	32
▶ 06272501	CB 627	2	20 (\approx 17/32)	0.303	7.7	45
▶ 06272751	CB 627	2	19 (\approx 23/32)	0.378	9.6	61
▶ 06282251	S CB 628	2	24 (\approx 34/38)	0.311	7.9	52
▶ 06282341	S CB 628	2	22 (\approx 42/38)	0.327	8.3	56
▶ 06282501	S CB 628	2	20 (\approx 68/38)	0.343	8.7	54
▶ 06274251	CB 627	2 x 2	24 (\approx 16/34)	0.287	7.3	41
▶ 06274341	CB 627	2 x 2	22 (\approx 7/30)	0.303	7.7	45
▶ 06274501	CB 627	2 x 2	20 (\approx 17/32)	0.386	9.8	70
▶ 06274751	CB 627	2 x 2	19 (\approx 23/32)	0.531	13.5	120
▶ 06284251	S CB 628	2 x 2	24 (\approx 34/38)	0.358	9.1	66
▶ 06284341	S CB 628	2 x 2	22 (\approx 42/38)	0.378	9.6	71
▶ 06284501	S CB 628	2 x 2	20 (\approx 68/38)	0.417	10.6	77

Other dimensions and colors are possible on request.



General construction:

Color code:	acc. to DIN VDE 47100
Insulation:	PE 2Y11 acc. to DIN VDE 0207 part 2
Screen:	tinned copper braiding

Technical data:

Peak operating voltage:	max. 350 V
Voltage:	UL: 300 V
Testing voltage:	1500 V
Min. bending radius:	7.5 x O.D.
Burning characteristics:	flame retardant and extinguishing acc. to IEC 60332-1-2 and EN 60332-1-2
Characteristic impedance at 1 MHz:	120 Ω (95 - 140 Ω)
Absence of harmful substances:	acc. to RoHS directive of the European Union see page O/30

J
32

	CB 627 	S CB 628 
▶ Conductor:	bare copper strands acc. to DIN VDE 0812	bare copper strands, extra fine wires
▶ Wrapping:	PETP foil	non-woven tape
▶ Inner jacket (nature):	–	SABIX®
▶ Jacket material (purple):	PVC, YÖ acc. to DIN VDE 0207 PUR, part 5	TPE
▶ Radiation resistance:	8 x 10 ⁷ cJ/kg	5 x 10 ⁷ cJ/kg
▶ Temperature range <i>static:</i> <i>flexing:</i>	UL: up to +80°C -30/+70°C -5/+70°C	UL: up to +80°C -40/+70°C -40/+70°C
▶ Zero halogen:	–	acc. to DIN VDE 0472 part 815 + IEC 60754-1
▶ Oil resistance:	very good - acc. to DIN VDE 0207	very good acc. to DIN VDE 0282 part 10
▶ Flexibility:	good	very good
▶ Application in cable tracks:	not recommended	recommended
▶ Chemical resistance: good against acids, alkalines, solvents, hydraulic liquids etc.	–	X
▶ Weather resistance:	medium	very good