

RM Cores (6298230121)

Part Number: 6298230121

98 RM CORE

RM (Rectangular Modulus) cores allow better shielding than E type geometries while also providing easier winding accessibility and better power dissipation than a pot core configuration. Fair-Rite's standard RM cores all have a solid center post and standard height, low profile and alternate materials are available upon request.

RM cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Weight indicated is per pair or set.

Weight: 13 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	22.75	± 0.45	0.896	
B	8.2	± 0.10	0.323	
C	10.8	± 0.20	0.425	
D	5.5	± 0.15	0.217	
E	17.3	± 0.30	0.681	
F	8.4	± 0.15	0.331	
G	9.8	min	0.386	min
J	19.1	± 0.40	0.752	





Figure 1

Chart Legend

$\Sigma l / A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross- Sectional Area, V_e : Effective Core Volume
 A_L : Inductance Factor 

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
A_L (nH)	3100 ±25%
A_e (cm ²)	0.6
$\Sigma l / A$ (cm ⁻¹)	6.7
l_e (cm)	4.03
V_e (cm ³)	2.419
A_{min} (cm ²)	0.554

A_L value is measured at 1 kHz, B < 10 gauss.