

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [63901-3200](#)
Status: **Active**
Description: FineAdjust™ Applicator for Male Flat Blade Crimp Terminals

Documents:
[RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Application Tooling
Series	T9999
Comments	See Tooling Specification (PDF) Above
Function	Crimp
Geographic Area	Global
Level of Automation	Semi-Automatic
More Detailed Tech Information	applicationtooling@molex.com
Product Name	FineAdjust™
Survey	www.molex.com//review/apptool_survey.html
Tool Type	FineAdjust Applicator
UPC	884982170179

Physical

Net Weight 5002.301/g

Material Info

Reference - Drawing Numbers

Application Tooling Documents

ATS-639013200, TM-638000029, TM-638000029CN, TM-638000029DE, TM-638000029FR, TM-638000029IT, TM-638000029JP, TM-638000029KR, TM-638000029MY, TM-638000029PL, TM-638000029RU, TM-638000029SK, TM-638000029SP, TM-638000029TH, TM-638000029TW, TM-638000029VN, TM-638004900, TM-638004900CN, TM-638004900SP



EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Low-Halogen Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[T9999Series](#)

Use With

[43178 Sabre™ Male Flat Blade Crimp Terminal, 14-16 AWG \(UL1007\)](#)

Application Tooling

Description

FAQ

Product #

Sabre™ Crimp Terminal, Male, 14-16 AWG or double 18-20 AWG, 4.57mm Max. Insulation Diameter, Reel Packaged, Tin (Sn) Plated Brass Contact	0431782002
Sabre™ Crimp Terminal, Male, 14-18 AWG, 4.57mm Insulation Diameter, Reel Packaged, Tin (Sn) Plated Brass Contact, Last-	0431786002

Make Wipe Length,
complies with the
UL1977 finger proof
access requirement

This document was generated on 04/26/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION