

 Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



 Active

Always EU RoHS/ELV Compliant (Statement of Compliance)

? MTA-156 Connectors
? Number of Positions = 6
? Mating Type = Header
? Wire -to -Board Application
? 3.96 mm Contact Centerline Spacing

[View all Features](#) | [Find Similar Products](#)

[Check Pricing & Availability](#)
[Search for Tooling](#)
[Product Feature Selector](#)
[Contact Us About This Product](#)

Product Drawings:

[MTA-156 HEADER ASSEMBLY, PLAIN, STRAIGHT, .045 SQUAR...](#)
(PDF, English)

? None Available

? None Available

? None Available

? None Available

? None Available

? Product Line Information

? Product Photo

? Tooling

List all Documents

Product Type Features:

- ? Product Type = MTA -156 Connectors
- ? Number of Positions = 6
- ? Mating Type = Header
- ? PCB Mount Angle = Vertical
- ? PCB Retention Feature = No
- ? Mating Polarization = Without
- ? Mating Connector Lock = Without
- ? Four Points of Contact = Without
- ? Shrouded = No
- ? Mounting Ears = Without
- ? PCB Thickness (mm [in]) = 1.60 [0.063]
- ? Post Size (mm [in]) = 1.14 [.045]

? Panel Attachment = Without

? Current Rating (Amps.) = 7
? Voltage Rating (VAC) = 600

? Solder Tail Contact Plating = Tin

? Termination (Solder) Post Length (mm [in]) = 3.18 [0.125]

? Narrow = No

? Post Number(s) Omitted = 2

? Contact Centerline Spacing (mm [in]) = 3.96
[0.156]

? Contact Shape = Square

? Contact Mating Area Plating Material = Tin

? Contact Material = Copper Alloy

? Housing Color = Natural
 ? Housing Flammability Rating = UL 94V -0
 ? Housing Material = Thermoplastic Polyester

? Backwall/Post Interruption(s) = Without

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

? Terminate To = Printed Circuit Board

? Application = Wire -to -Board

? Brand = AMP