

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0643202311](#)  
**Status:** **Active**  
**Overview:** CMC and CMX Sealed, Hybrid, Modular Connectors  
**Description:** .635mm, 1.50mm, CMC Receptacle, 36 Circuits, Left Wire Output, Black Coding, Mat Sealed, Row 1 Closed

**Documents:**

<a href="#">3D Model</a>	<a href="#">Application Specification AS-98420-002-001 (PDF)</a>
<a href="#">3D Model (PDF)</a>	<a href="#">Application Specification AS-98420-002-CH-001 (PDF)</a>
<a href="#">Drawing (PDF)</a>	<a href="#">Application Specification AS-98420-002-FR-001 (PDF)</a>
<a href="#">Application Specification AS-64319-002-001 (PDF)</a>	<a href="#">Application Specification AS-98420-002-SP-001 (PDF)</a>
<a href="#">Application Specification AS-64319-002-CH-001 (PDF)</a>	<a href="#">Packaging Specification PK-64320-001-001 (PDF)</a>
<a href="#">Application Specification AS-64319-002-FR-001 (PDF)</a>	<a href="#">Datasheet (PDF)</a>
<a href="#">Application Specification AS-64319-002-SP-001 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>

**Application tooling part link**

Application Tooling Part Link	63812-1100
Application Tooling Part Link	63824-1200

**General**

Product Family	Crimp Housings
Series	<a href="#">64320</a>
Application	Automotive, Power, Wire-to-Board
Comments	* Current tested on a 5 terminals loaded connector, current for temperature increase of 40°C . Current max = 6.0A for 0.635mm Terminal (0.75mm <sup>2</sup> wire) and 12.0A for 1.50mm Terminal (2.00mm <sup>2</sup> wire) *

[More Detailed Tech Information](#)

**Overview**

Product Name	<a href="#">CMC and CMX Sealed, Hybrid, Modular Connectors</a>
UPC	CMC 883906131111

**Physical**

Circuits (maximum)	36
Circuits Detail	6 x 1.5mm, 30 x 0.635mm terminals
Color - Resin	Black
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Polyester
Net Weight	36.000/g
Number of Rows	3
Packaging Type	Carton
Panel Mount	No
Pitch - Mating Interface	2.54mm, 3.70mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +125°C



*Series image - Reference only*

**EU ELV**

**Compliant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2021)10043-DC (17  
Jan 2022)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Compliant

Not Contained

**Search Parts in this Series**

[64320 Series](#)

**Mates With**

CMC Header [477320361](#) , [36638](#)

**Use With**

CMC CP Female Terminal [64322](#)  
(0.635mm), [64323](#) (1.50mm) . CMC Wire  
Cap [643201301](#) . Sealing Plugs [643251010](#)  
, [643251023](#)

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

**Description**

**Product #**

Continuity Test Pen	<a href="#">638121100</a>
---------------------	---------------------------

Assembly

Unlocking Tool	<a href="#">638241200</a>
----------------	---------------------------

for CMC and

**Electrical**

Current - Maximum per Contact 12.0A, 2.5A

**Solder Process Data**

Lead-freeProcess Capability N/A

**Material Info**

**Reference - Drawing Numbers**

Application Specification AS-64319-002-001, AS-64319-002-CH-001,  
AS-64319-002-FR-001, AS-64319-002-SP-001,  
AS-98420-002-001, AS-98420-002-CH-001,  
AS-98420-002-FR-001, AS-98420-002-SP-001  
Packaging Specification PK-64320-001-001  
Sales Drawing 643200003-000, SD-64320-003-001

This document was generated on 04/14/2022

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**