

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [64324-1139](#)  
**Status:** **Active**  
**Overview:** CMC Sealed, Hybrid, Modular Connectors and Headers  
**Description:** 2.80mm , CMC CP Female Terminal, Tin plated; Selective 1.27µm Gold in Contact Area, for Tab Dimensions 2.8mm x 0.8mm , Wire Size >1mm<sup>2</sup> to 2mm<sup>2</sup>

**Documents:**

<a href="#">3D Model</a>	<a href="#">Application Specification AS-64318-002-FR (PDF)</a>
<a href="#">Drawing (PDF)</a>	<a href="#">Application Specification AS-64318-002-SP (PDF)</a>
<a href="#">Product Specification PS-64318-001 (PDF)</a>	<a href="#">Application Specification AS-64324-001 (PDF)</a>
<a href="#">Product Specification PS-64321-001 (PDF)</a>	<a href="#">Packaging Specification PK-98910-001 (PDF)</a>
<a href="#">Product Specification PS-64326-001 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>
<a href="#">Application Specification AS-64318-002 (PDF)</a>	

**General**

Product Family	Crimp Terminals
Series	64324
Application	Power
Comments	* Current tested on a fully loaded connector, current for temperature increase of 40°C. Current max = 21A for 2.80mm Terminal (5.00mm <sup>2</sup> wire)
Crimp Quality Equipment	Yes
Overview	<a href="#">CMC Sealed, Hybrid, Modular Connectors and Headers</a>
Product Name	CMC, CP Terminal
UPC	883906128456

**Physical**

Gender	Female
Material - Metal	High Copper
Material - Plating Mating	Tin
Material - Plating Termination	Gold
Packaging Type	Reel
Plating min - Mating	1.270µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	2.10mm-2.80mm
Wire Size AWG	14, 16
Wire Size mm <sup>2</sup>	> 1.0-2.0


**Electrical**

Current - Maximum per Contact	21A
Voltage - Maximum	250V AC

**Material Info**

**Reference - Drawing Numbers**

Application Specification	AS-64318-002, AS-64318-002-FR, AS-64318-002-SP, AS-64324-001
Packaging Specification	PK-98910-001
Product Specification	PS-64318-001, PS-64321-001, PS-64326-001
Sales Drawing	SD-64324-001



**EU RoHS**

**ELV and RoHS Compliant**

**REACH SVHC**

Not Reviewed

**Low-Halogen Status**

**Low-Halogen**

**China RoHS**



**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

**Search Parts in this Series**

[64324Series](#)

**Mates With**

CMC Connector [64318](#) , [64321](#) , [64326](#) , [643251175](#)

**Use With**

CMC Connector [64318](#) , [64321](#) , [64326](#) , [643251175](#)

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

<b>Description</b>	<b>Product #</b>
--------------------	------------------

Hand Crimp Tool for CP 2.8 Receptacle 14-16 AWG Type TXL Wire and >1.00-2.00mm <sup>2</sup> Type ID & ID Wire with 2.80mm,	<a href="#">0638119700</a>
--	----------------------------

CMC Wire Seal	
Receptacle	
Extraction Tool	<u>0638132500</u>
Mini-Mac™	<u>0638951100</u>
Applicator for	
CP2.8 Terminals,	
>1.00-2.00mm <sup>2</sup> ID &	
IR Wire	

This document was generated on 02/11/2013

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**