

SIMATIC ET 200SP, DIGITAL INPUT MODULE, DI 16X 24VDC STANDARD, FITS TO BU-TYPE A0, COLOR CODE CC00, MODULE DIAGNOSIS



General information	
Product type designation	ET 200SP, DI 16x 24 V DC ST, PU 1
Firmware version	V1.1
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V13 SP1
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 / -
<ul style="list-style-type: none"> <li>PCS 7 configurable/integrated as of version</li> </ul>	V8.1 SP1
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	GSD Revision 5
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	GSDML V2.3
Operating mode	
<ul style="list-style-type: none"> <li>DI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Counter</li> </ul>	No

- Oversampling
- MSI

No

No

### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes

### Input current

Current consumption, max.	90 mA
---------------------------	-------

### Encoder supply

Short-circuit protection	No
--------------------------	----

#### 24 V encoder supply

- 24 V No
- Short-circuit protection No

### Power loss

Power loss, typ.	1.7 W
------------------	-------

### Address area

#### Address space per module

- Address space per module, max. 2 byte; + 2 bytes for QI information

### Hardware configuration

#### Automatic encoding

- Mechanical coding element Yes

#### Selection of BaseUnit for connection variants

- 1-wire connection BU type A0
- 2-wire connection BU type A0 + external terminals
- 3-wire connection BU type A0 + external terminals
- 4-wire connection BU type A0 + external terminals

### Digital inputs

Number of digital inputs	16
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input characteristic curve in accordance with IEC 61131, type 2	No
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Pulse extension	No

#### Input voltage

- Type of input voltage DC
- Rated value (DC) 24 V

<ul style="list-style-type: none"> <li>• for signal "0"</li> <li>• for signal "1"</li> </ul>	-30 to +5V +11 to +30V
<b>Input current</b>	
<ul style="list-style-type: none"> <li>• for signal "1", typ.</li> </ul>	2.5 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— parameterizable	Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms (in each case + delay of 30 to 500 $\mu$ s, depending on line length)
— at "0" to "1", min.	0.05 ms
— at "0" to "1", max.	20 ms
— at "1" to "0", min.	0.05 ms
— at "1" to "0", max.	20 ms
for interrupt inputs	
— parameterizable	No
for counter/technological functions	
— parameterizable	No
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> <li>• unshielded, max.</li> </ul>	1 000 m 600 m
<b>Encoder</b>	
<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>• 2-wire sensor</li> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul>	Yes 1.5 mA
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	No
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> </ul>	Yes
<b>Diagnostic messages</b>	
<ul style="list-style-type: none"> <li>• Diagnostic information readable</li> <li>• Monitoring the supply voltage</li> <li>— parameterizable</li> <li>• Monitoring of encoder power supply</li> <li>• Wire-break</li> <li>• Short-circuit</li> <li>• Group error</li> </ul>	Yes Yes Yes No Yes; Module-by-module, optional protective circuit for preventing wire-break diagnostics in the case of simple encoder contacts: 25 kOhm to 45 kOhm No Yes

Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; Green LED
• for channel diagnostics	No
• for module diagnostics	Yes; green/red DIAG LED

Potential separation	
Potential separation channels	
• between the channels	No
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	No

Isolation	
Isolation tested with	707 V DC (type test)

Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm

Weights	
Weight, approx.	28 g
<b>last modified:</b>	08/12/2017