

SIMATIC DP, Interface module IM 151-3 PN ST for ET 200S  
 Transmission rate 100 Mbit/s max. 63 power, electronic or motor  
 starter modules up to 2 m width can be connected; 2x bus  
 connections via RJ45 incl. termination module



General information	
Product type designation	IM 151-3 PN ST
Configuration control	
via dataset	Yes
Supply voltage	
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Input current	
from supply voltage 1L+, max.	200 mA
Power loss	
Power loss, typ.	3.3 W
Address area	
Addressing volume	
• Inputs	256 byte
• Outputs	256 byte
Interfaces	

Number of PROFINET interfaces	1
Transmission rate, max.	100 Mbit/s
<b>1. Interface</b>	
Autonegotiation	Yes
Autocrossing	Yes
<b>Interface types</b>	
• RJ 45 (Ethernet)	Yes
• Number of ports	2
<b>PROFINET IO Device</b>	
<b>Services</b>	
— IRT	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
<b>Protocols</b>	
Supports protocol for PROFINET IO	Yes
<b>Protocols (Ethernet)</b>	
• TCP/IP	No
• SNMP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes
<b>Redundancy mode</b>	
<b>Media redundancy</b>	
— MRP	Yes
<b>Interrupts/diagnostics/status information</b>	
<b>Diagnostics indication LED</b>	
• Bus fault BF (red)	Yes
• Group error SF (red)	Yes
• Monitoring 24 V voltage supply ON (green)	Yes
• Connection to network LINK (green)	Yes
<b>Potential separation</b>	
between backplane bus and electronics	No
between supply voltage and electronics	No
between Ethernet and electronics	Yes
<b>Isolation</b>	
Isolation tested with	500 V
<b>Standards, approvals, certificates</b>	
CE mark	Yes

UL approval	Yes
-------------	-----

### Ambient conditions

Ambient temperature during operation	
• min.	0 °C
• max.	60 °C

### Dimensions

Width	60 mm
Height	119.5 mm
Depth	75 mm

### Weights

Weight, approx.	150 g
<b>last modified:</b>	12/09/2020