

SIMATIC ET 200SP, PROFINET bundle IM, IM 155-6PN ST, max. 32 I/O modules and 16 ET 200AL modules, single hot swap, bundle consists of: Interface module (6ES7155-6AU00-0BN0), Server module (6ES7193-6PA00-0AA0), BusAdapter BA 2xRJ45 (6ES7193-6AR00-0AA0)



Figure similar

General information	
Product type designation	IM 155-6 PN ST
Firmware version	V3.3
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> Module swapping during operation (hot swapping) 	Yes; Single hot swapping
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V13 SP1
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 SP4 and higher
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	V2.3 / -
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V

permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms

Input current	
Current consumption, max.	450 mA
Inrush current, max.	3.7 A
I^2t	0.09 A ² ·s

Power loss	
Power loss, typ.	1.9 W

Address area	
Address space per module	
• Address space per module, max.	256 byte; per input / output
Address space per station	
• Address space per station, max.	512 byte; Dependent on configuration

Hardware configuration	
Rack	
• Modules per rack, max.	32; + 16 ET 200AL modules
Submodules	
• Number of submodules per station, max.	256

Interfaces	
Number of PROFINET interfaces	1; 2 ports (switch)

1. Interface	
Interface types	
• Number of ports	2
• integrated switch	Yes
• RJ 45 (Ethernet)	Yes; Pre-assembled BusAdapter BA 2x RJ45
• BusAdapter (PROFINET)	Yes; Applicable BusAdapter: BA 2x RJ45, BA 2x FC
Functionality	
• PROFINET IO Device	Yes
• Open IE communication	Yes
• Media redundancy	Yes; PROFINET MRP

Interface types	
RJ 45 (Ethernet)	
• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• 10 Mbps	No
• 100 Mbps	Yes; PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• Autonegotiation	Yes
• Autocrossing	Yes

Protocols	
PROFINET IO Device	
Services	
— Isochronous mode	No
— Open IE communication	Yes
— IRT	Yes; with send cycles of between 250 µs and 4 ms in increments of 125 µs
— PROFINergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
Redundancy mode	
— MRP	Yes
— MRPD	No
— PROFINET system redundancy (S2)	No
Open IE communication	
• TCP/IP	Yes
• SNMP	Yes
• LLDP	Yes
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Equidistance	No
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	Yes
Diagnostic functions	Yes
Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• MAINT LED	Yes; yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Connection display LINK TX/RX	Yes; 2x green link LEDs on BusAdapter
Potential separation	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes
between supply and all other circuits	Yes
Isolation	
Isolation tested with	707 V DC between supply voltage and electronics; 1 500 V AC between Ethernet and electronics

Standards, approvals, certificates

Network loading class	2
Security level	According to Security Level 1 Test Cases V1.1.1

Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	50 °C

Connection method

ET-Connection	
• via BU/BA Send	Yes; + 16 ET 200AL modules

Dimensions

Width	50 mm
Height	117 mm
Depth	74 mm

Weights

Weight, approx.	191 g; IM155PN ST with BA 2x RJ45 (mounted)
last modified:	01/29/2018