

connector, female, 2x2-pole, ET200SP, interface module, KP32F, PN-PN coupler, grid size 5.08 mm cage clamp technology, internally bridged, color-coded 10 units per packing unit



General information	
Product type designation	Connector, female, 2x2-pin
Installation type/mounting	
Wall mounting/direct mounting	Yes; can be plugged into SIMATIC HMI device
Supply voltage	
Rated value (DC)	24 V
Interfaces	
HMI-side interface	
<ul style="list-style-type: none"> Number of pins HMI-side 	2; Outgoing side jumpered internally, color-coded
Device-side interface	
<ul style="list-style-type: none"> Number of pins device-side 	4; Female, spring-loaded terminals 0.75 mm ²
Standards, approvals, certificates	
CE mark	Yes
RoHS conformity	Yes
China RoHS compliance	Yes
Ambient conditions	
Ambient temperature during storage/transportation	

- min. -20 °C
- max. 70 °C

Mechanics/material

Design of housing plastic

Dimensions

Width 10 mm

Height 22 mm

Thickness 25 mm

Scope of supply

Delivery quantity in pieces 10

Other

Merchandise No

Manufacturer name SIEMENS AG

Manufacturer's address Gleiwitzerstraße 555, 90475 Nuremberg, Germany

Note: For ET 200S, interface module, KP32F, PN/PN coupler

Usable in the following products

- Product 1 [6AV3688-3EH47-0AX0](#)
- Product 2 6AV7863*
- Product 3 6AV7862-2*

last modified: 12/09/2020