

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [70929-2009](#)
Status: **Active**
Overview: [LFH™](#)
Description: 1.27mm Pitch LFH™ Matrix 50 Plug Cable Kit, Subassembly, 60 Circuits, Bright Nickel (Ni) Front Shell Plating

Documents:

3D Model	Application Specification AS-70929-001 (PDF)
Drawing (PDF)	Application Specification AS-71624-001 (PDF)
Product Specification PS-70928 (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E29179

General

Product Family	I/O Connectors
Series	70929
Application	Wire-to-Board
Comments	I/O Plug Connector Subassembly Use Tool 62200-1500 for inserting sticks into subassembly 70984 Terminal Sticks Supplied Separately
Component Type	I/O Plug Connector Subassembly
Overview	LFH™
Product Name	LFH™
Type	N/A
UPC	822350303040

Physical

Boot Color	N/A
Circuits (Loaded)	60
Circuits (maximum)	60
Color - Resin	Black
Durability (mating cycles max)	500
Flammability	94V-0
Gender	Plug
Lock to Mating Part	None
Material - Metal	Aluminum
Material - Plating Mating	N/A
Material - Resin	High Temperature Thermoplastic
Net Weight	4.846/g
Number of Rows	4
Orientation	Vertical
PCB Retention	N/A
Packaging Type	Tray
Panel Mount	Yes
Pitch - Mating Interface	1.27mm
Pitch - Termination Interface	1.27mm
Polarized to Mating Part	Yes
Polarized to PCB	N/A
Ports	1
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-20°C to +80°C
Termination Interface: Style	N/A
Waterproof / Dustproof	No



EU RoHS

ELV and RoHS Compliant

REACH SVHC

Not Reviewed

Low-Halogen Status

Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[70929Series](#)

Mates With

[70928 LFH™ Receptacle](#)

Use With

[70984 Terminal Stick](#), [71245 ClampShell](#), [71628 Guide Pin](#), [Guide Sleeve 71629](#) or [71771](#), [70982 Hex Screw Kit](#)

Electrical

Current - Maximum per Contact	1A
Shield Type	Full Shield
Shielded	Yes
Voltage - Maximum	40V AC (RMS)

Material Info**Reference - Drawing Numbers**

Application Specification	AS-70929-001, AS-71624-001
Product Specification	PS-70928, RPS-70928-002
Sales Drawing	SDA-70929-20**

This document was generated on 04/12/2013

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION