

R71MN4220AA30K

aka 71MN4220AA30K

Capacitor, film, 2.2 uF, +/-10% Tol, -40/+110C, Power Factor Correction, 220VAC, Lead Spacing=22.5 mm



Dimensions (mm)

Specifications

| ID | Dimension | Tolerance | Manufacturer: | KEMET |
|----|-----------|-----------|-----------------------------|--------------------------|
| L | 26.5 | +0.3 | Brand: | Arcotronics |
| H | 20 | +0.1 | Capacitance: | 2.2 uF |
| T | 11 | +0.2 | Temperature Range: | -40/+110C |
| S | 22.5 | +/-0.4 | Rated Temperature: | 105C |
| LL | 4 | +2 | Voltage @ rated temp: | 420V |
| F | 0.8 | +/-0.05 | Voltage AC: | 220VAC |
| | | | Tolerance: | +/-10% |
| | | | Body Type: | Radial Box |
| | | | Construction: | Wound |
| | | | Application: | Power Factor Correction |
| | | | Dielectric: | Metallized Polypropylene |
| | | | Dissipation Factor @ 1 kHz: | 0.1% |
| | | | Insulation Resistance: | 13.64 GOhm |
| | | | Inductance: | 18 nH |
| | | | Maximum dVdT: | 100v/us |
| | | | Maximum K0: | 84000V^2/us |
| | | | Package Kind: | Bulk |
| | | | Package Type: | Bag |
| | | | Package Quantity: | 360 |